



## SAFETY DATA SHEET

Black Epoxy Repair Filler

Page: 1

Compilation date: 25/06/2015

Revision date: 21/03/2017

Revision No: 7

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** Black Epoxy Repair Filler

**Product code:** EP-FILL-A

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC1: Adhesives, sealants. PC9a: Coatings and paints, thinners, paint removers. PC9b: Fillers, putties, plasters, modelling clay. PC32: Polymer preparations and compounds. PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of preparations\* and articles (multistage and/or significant contact) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring PROC19: Hand-mixing with intimate contact and only PPE available ERC2: Formulation of preparations\* ERC3: Formulation in materials ERC5: Industrial use resulting in inclusion into or onto a matrix ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** Easy Composites Ltd  
Unit 39, Park Hall Business Village  
Longton, Stoke on Trent  
Staffordshire  
ST3 5XA  
United Kingdom

**Tel:** +44 (0) 1782 454499

**Email:** sales@easycomposites.co.uk

# SAFETY DATA SHEET

Black Epoxy Repair Filler

Page: 2

## 1.4. Emergency telephone number

**Emergency tel:** +44 (0) 1782 454499  
(office hours only)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317

**Most important adverse effects:** Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.  
Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

#### Label elements:

**Hazard statements:** H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H411: Toxic to aquatic life with long lasting effects.

**Hazard pictograms:** GHS07: Exclamation mark  
GHS09: Environmental



**Signal words:** Warning

**Precautionary statements:** P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.  
P264: Wash hands thoroughly after handling.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P302+352: IF ON SKIN: Wash with plenty of water/.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321: Specific treatment (see instructions on this label).

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

**Hazardous ingredients:**

[cont...]

# SAFETY DATA SHEET

Black Epoxy Repair Filler

Page: 3

## BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

EINECS	CAS	PBT / WEL	CLP Classification	Percent
500-033-5	25068-38-6	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	>50%

## 1,3-PROPANEDIOL, 2,2-BIS(HYDROXYMETHYL)-, POLYMER WITH 2-(CHLOROMETHYL)OXRIANE

608-564-5	30973-88-7	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1: H317	1-25%
-----------	------------	---	--	-------

## 1,4-BIS(2,3-EPOXYPROPOXY) BUTANE

219-371-7	2425-79-8	-	Acute Tox. 4: H332; Acute Tox. 4: H312; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317	1-25%
-----------	-----------	---	---	-------

## PROPYLENE CARBONATE

203-572-1	108-32-7	-	Eye Irrit. 2: H319	1-25%
-----------	----------	---	--------------------	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** Nausea and stomach pain may occur.

**Inhalation:** There may be a feeling of tightness in the chest with shortness of breath. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Show this safety data sheet to the doctor in attendance.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Water spray. Water fog. Dry chemical powder. Carbon dioxide. Alcohol or polymer foam. Alcohol resistant foam.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

[cont...]

# SAFETY DATA SHEET

Black Epoxy Repair Filler

Page: 4

## 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Mark out the contaminated area with signs and prevent access to unauthorised personnel. Refer to section 8 of SDS for personal protection details.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Mix with sand or vermiculite. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS. Refer to section 13 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area.

**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Workplace exposure limits:** No data available.

### DNEL/PNEC Values

**Hazardous ingredients:**

#### PROPYLENE CARBONATE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	70.53 mg/m <sup>3</sup>	Workers	Systemic
DNEL	Inhalation	20 mg/m <sup>3</sup>	Workers	Local

[cont...]

# SAFETY DATA SHEET

Black Epoxy Repair Filler

Page: 5

DNEL	Dermal	20 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation	17.4 mg/m <sup>3</sup>	Consumers	Systemic
DNEL	Inhalation	10 mg/m <sup>3</sup>	Consumers	Local
DNEL	Dermal	10 mg/kg bw/day	Consumers	Systemic
DNEL	Oral	10	Consumers	Systemic
PNEC	Fresh water	0.9 mg/l	-	-
PNEC	Marine water	0.09 mg/l	-	-
PNEC	Microorganisms in sewage treatment	7400 mg/l	-	-
PNEC	Soil (agricultural)	0.81 mg/kg d.w.	-	-

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Impermeable gloves.

**Eye protection:** Safety glasses.

**Skin protection:** Protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Pale yellow

**Odour:** Characteristic odour

**Evaporation rate:** No data available.

**Oxidising:** No data available.

**Solubility in water:** No data available.

**Viscosity:** 1100 mPas (25°C)

**Boiling point/range°C:** No data available.

**Flammability limits %: lower:** No data available.

**Flash point°C:** No data available.

**Autoflammability°C:** No data available.

**Relative density:** 1.16 - 1.21

**VOC g/l:** No data available.

**Melting point/range°C:** No data available.

**upper:** No data available.

**Part.coeff. n-octanol/water:** No data available.

**Vapour pressure:** No data available.

**pH:** No data available.

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

[cont...]

# SAFETY DATA SHEET

Black Epoxy Repair Filler

Page: 6

## 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Polymerisation may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

## 10.5. Incompatible materials

**Materials to avoid:** Amines.

## 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Hazardous ingredients:

#### BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

#### 1,4-BIS(2,3-EPOXYPROPOXY) BUTANE

ORL	RAT	LD50	1134	mg/kg
-----	-----	------	------	-------

#### PROPYLENE CARBONATE

DERMAL	RBT	LD50	>2000	mg/kg
ORL	RAT	LD50	33520	µl/kg

#### Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** Nausea and stomach pain may occur.

**Inhalation:** There may be a feeling of tightness in the chest with shortness of breath. Exposure may cause coughing or wheezing.

[cont...]

# SAFETY DATA SHEET

Black Epoxy Repair Filler

Page: 7

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

**Hazardous ingredients:**

**1,3-PROPANEDIOL, 2,2-BIS(HYDROXYMETHYL)-, POLYMER WITH 2-(CHLOROMETHYL)OXIRANE**

Golden Orfe (Leuciscus idus)	96H LC50	460	mg/l
------------------------------	----------	-----	------

**PROPYLENE CARBONATE**

Daphnia magna	48H EC50	> 1000	mg/l
FISH (Cyprinus carpio)	96H LC0	> 1000	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H EC50	> 900	mg/l

### 12.2. Persistence and degradability

**Persistence and degradability:** No data available.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data available.

### 12.4. Mobility in soil

**Mobility:** No data available.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Toxic to aquatic organisms.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Disposal of packaging:** Arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN3082

### 14.2. UN proper shipping name

**Shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

[cont...]

# SAFETY DATA SHEET

Black Epoxy Repair Filler

Page: 8

(Epoxy Resin)

## 14.3. Transport hazard class(es)

Transport class: 9

## 14.4. Packing group

Packing group: III

## 14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

## 14.6. Special precautions for user

Tunnel code: E

Transport category: 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H411: Toxic to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.



## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** Black Epoxy Repair Filler Hardener

**Product code:** EP-FILL-B

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC1: Adhesives, sealants. PC9a: Coatings and paints, thinners, paint removers. PC9b: Fillers, putties, plasters, modelling clay. PC32: Polymer preparations and compounds. PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of preparations\* and articles (multistage and/or significant contact) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring PROC19: Hand-mixing with intimate contact and only PPE available ERC2: Formulation of preparations\* ERC3: Formulation in materials ERC5: Industrial use resulting in inclusion into or onto a matrix ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

### 1.3. Details of the supplier of the safety data sheet

**Company name:** Easy Composites Ltd  
Unit 39, Park Hall Business Village  
Longton, Stoke on Trent  
Staffordshire  
ST3 5XA  
United Kingdom  
**Tel:** +44 (0) 1782 454499  
**Email:** sales@easycomposites.co.uk

# SAFETY DATA SHEET

Black Epoxy Repair Filler Hardener

Page: 2

## 1.4. Emergency telephone number

**Emergency tel:** +44 (0) 1782 454499  
(office hours only)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** Acute Tox. 3: H311; Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Aquatic Chronic 3: H412; Repr. 2: H361fd; Skin Corr. 1B: H314; Skin Sens. 1: H317; STOT RE 1: H372

**Most important adverse effects:** Harmful if swallowed. Toxic in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of damaging fertility. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

#### Label elements:

**Hazard statements:** H302: Harmful if swallowed.  
H311: Toxic in contact with skin.  
H314: Causes severe skin burns and eye damage.  
H317: May cause an allergic skin reaction.  
H361fd: Suspected of damaging fertility. Suspected of damaging the unborn child.  
H372: Causes damage to organs through prolonged or repeated exposure.  
H400: Very toxic to aquatic life.  
H410: Very toxic to aquatic life with long lasting effects.  
H412: Harmful to aquatic life with long lasting effects.

**Hazard pictograms:** GHS05: Corrosion  
GHS06: Skull and crossbones  
GHS08: Health hazard  
GHS09: Environmental



**Signal words:** Danger

**Precautionary statements:** P260: Do not breathe dust/fumes/gas/mist/vapours/spray.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P301+312: IF SWALLOWED: Call a doctor if you feel unwell.  
P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  
P302+352: IF ON SKIN: Wash with plenty of water/.  
P361+364: Take off immediately all contaminated clothing and wash it before reuse.

[cont...]

# SAFETY DATA SHEET

Black Epoxy Repair Filler Hardener

Page: 3

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

AMINOETHYLPIPERAZINE - REACH registered number(s): 01-2119471486-30

EINECS	CAS	PBT / WEL	CLP Classification	Percent
205-411-0	140-31-8	-	Acute Tox. 4: H302; Acute Tox. 3: H311; Skin Corr. 1B: H314; Eye Dam. 1: H318; Skin Sens. 1: H317; Repr. 2: H361; STOT RE 1: H372; Aquatic Chronic 3: H412	>50%

NONYLPHENOL

246-672-0	25154-52-3	-	Repr. 2: H361fd; Acute Tox. 4: H302; Skin Corr. 1B: H314; Aquatic Acute 1: H400; Aquatic Chronic 1: H410	25-50%
-----------	------------	---	--	--------

TRIETHANOLAMINE - REACH registered number(s): 01-2119488930-28

203-049-8	102-71-6	-	Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT RE 2: H373	1-25%
-----------	----------	---	---	-------

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL - REACH registered number(s): 01-2119560597-27

202-013-9	90-72-2	-	Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315	1-25%
-----------	---------	---	--	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Transfer to hospital as soon as possible.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** Absorption through the lungs can occur causing symptoms similar to those of ingestion.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

[cont...]

# SAFETY DATA SHEET

Black Epoxy Repair Filler Hardener

Page: 4

## 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Not applicable.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid the formation or spread of mists in the air. Avoid direct contact with the substance.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

[cont...]

# SAFETY DATA SHEET

Black Epoxy Repair Filler Hardener

Page: 5

## 8.1. Control parameters

**Workplace exposure limits:** No data available.

## DNEL/PNEC Values

**Hazardous ingredients:**

### AMINOETHYLPIPERAZINE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	21.4 mg/m <sup>3</sup>	Workers	Systemic
DNEL	Inhalation	5.3 mg/m <sup>3</sup>	Consumers	Systemic
PNEC	Fresh water	0.058 mg/l	-	-
PNEC	Marine water	0.0058 mg/l	-	-
PNEC	Fresh water sediments	215 mg/kg	-	-
PNEC	Marine sediments	21.5 mg/kg	-	-
PNEC	Soil (agricultural)	42.9 mg/kg	-	-
PNEC	Microorganisms in sewage treatment	250 mg/l	-	-

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Respiratory protection not required.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Environmental:** The floor of the storage room must be impermeable to prevent the escape of liquids.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Pale green

**Odour:** Characteristic odour

**Evaporation rate:** No data available.

**Oxidising:** No data available.

**Solubility in water:** No data available.

**Viscosity:** 150 mPas (25°C)

**Boiling point/range°C:** No data available.

**Flammability limits %: lower:** No data available.

**Flash point°C:** No data available.

**Autoflammability°C:** No data available.

**Relative density:** 0.96 - 1.01

**VOC g/l:** No data available.

**Melting point/range°C:** No data available.

**upper:** No data available.

**Part.coeff. n-octanol/water:** No data available.

**Vapour pressure:** No data available.

**pH:** No data available.

[cont...]

# SAFETY DATA SHEET

Black Epoxy Repair Filler Hardener

Page: 6

## 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

Conditions to avoid: Heat.

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

Hazardous ingredients:

#### AMINOETHYLPIPERAZINE

DERMAL	RBT	LD50	866	mg/kg
ORAL	RBT	LD50	2097	mg/kg

#### NONYLPHENOL

ORL	MUS	LD50	1231	mg/kg
ORL	RAT	LD50	580	mg/kg

#### 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

ORAL	RAT	LD50	2169	mg/kg
------	-----	------	------	-------

Relevant hazards for product:

Hazard	Route	Basis
--------	-------	-------

[cont...]

# SAFETY DATA SHEET

Black Epoxy Repair Filler Hardener

Page: 7

Acute toxicity (ac. tox. 4)	ING	Hazardous: calculated
Acute toxicity (ac. tox. 3)	DRM	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
Reproductive toxicity	--	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** Absorption through the lungs can occur causing symptoms similar to those of ingestion.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

#### Hazardous ingredients:

#### AMINOETHYLPIPERAZINE

Daphnia magna	48H EC50	58	mg/l
FISH	96H LC50	2190	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H EC50	> 1000	mg/l

#### 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

COMMON CARP (Cyprinus carpio)	96H LC50	175	mg/l
COMMON CARP (Cyprinus carpio)	24H LC50	249	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	24H LC50	222	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC0	180	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC100	240	mg/l
Scenedesmus Subspicatus	72H EC50	84	mg/l

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

[cont...]

# SAFETY DATA SHEET

Black Epoxy Repair Filler Hardener

Page: 8

## 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Disposal of packaging:** Arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN2735

### 14.2. UN proper shipping name

**Shipping name:** AMINES, LIQUID, CORROSIVE, N.O.S.  
(Aliphatic amines)

### 14.3. Transport hazard class(es)

**Transport class:** 8

### 14.4. Packing group

**Packing group:** III

### 14.5. Environmental hazards

**Environmentally hazardous:** Yes

**Marine pollutant:** Yes

### 14.6. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** E

**Transport category:** 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

[cont...]



# SAFETY DATA SHEET

Black Epoxy Repair Filler Hardener

Page: 9

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H302: Harmful if swallowed.

H311: Toxic in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H361: Suspected of damaging fertility or the unborn child <state specific effect if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H361fd: Suspected of damaging fertility. Suspected of damaging the unborn child.

H372: Causes damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.