

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Product name : CLEARPOL Extra Clear ISO NPG Polyester Gelcoat  
 Product code : PYGC  
 Product group : Trade product

#### 1.2.

##### 1.2.1. Relevant identified uses

Use of the substance/mixture : Coating

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Easy Composites Ltd  
 Unit 39, Park Hall Business Village, Stoke on Trent, Staffordshire, ST3 5XA. United Kingdom.  
 Tel: +44 (0)1782 454499  
[sales@easycomposites.co.uk](mailto:sales@easycomposites.co.uk) - [www.easycomposites.co.uk](http://www.easycomposites.co.uk)

#### 1.4.

Emergency number : ORFILA - 0033 1 45 42 59 59

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Germ cell mutagenicity, Category 1B	H340
Carcinogenicity, Category 1B	H350
Reproductive toxicity, Category 2	H361
Specific target organ toxicity — Repeated exposure, Category 1	H372

Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) : Danger

Hazardous ingredients : methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate; Styrene; Low boiling point naphtha

Hazard statements (CLP) : H226 - Flammable liquid and vapour  
 H315 - Causes skin irritation  
 H317 - May cause an allergic skin reaction

# CLEARPOL EXTRA CLEAR ISO NPG POLYESTER GELCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)	H319 - Causes serious eye irritation
	H332 - Harmful if inhaled
	H340 - May cause genetic defects
	H350 - May cause cancer
	H361 - Suspected of damaging fertility or the unborn child
	H372 - Causes damage to organs through prolonged or repeated exposure
	P280 - Wear protective gloves, protective clothing, eye protection
	P241 - Use explosion-proof electrical equipment
	P271 - Use only outdoors or in a well-ventilated area
	P370+P378 - In case of fire: Use Water fog, foam, extinguishing powder, carbon dioxide (CO2) for extinction
	P264 - Wash hands thoroughly after handling
	P210 - Keep away from heat, hot surfaces, sparks, open flames. - No smoking

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Styrene	(CAS-No.) 100-42-5 (EC-No.) 202-851-5 (EC Index-No.) 601-026-00-0 (REACH-no) 01-2119457861-32	40 - 50	Flam. Liq. 3, H226 Repr. 2, H361d Acute Tox. 4 (Inhalation), H332 STOT RE 1, H372 Skin Irrit. 2, H315 Eye Irrit. 2, H319
methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate	(CAS-No.) 80-62-6 (EC-No.) 201-297-1 (EC Index-No.) 607-035-00-6 (REACH-no) 01-2119452498-28	1 - 5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335
Low boiling point naphtha	(CAS-No.) 64742-95-6 (EC-No.) 265-199-0 (EC Index-No.) 649-356-00-4	< 1	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
	(CAS-No.) 3164-85-0 (EC-No.) 221-625-7	< 1	Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 2, H361
ethanediol, ethylene glycol substance with a Community workplace exposure limit	(CAS-No.) 107-21-1 (EC-No.) 203-473-3 (EC Index-No.) 603-027-00-1 (REACH-no) 01-2119472426-35	< 1	Acute Tox. 4 (Oral), H302

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# CLEARPOL EXTRA CLEAR ISO NPG POLYESTER GELCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Use water spray or fog for cooling exposed containers. Prevent entry to sewers and public waters.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Do not breathe vapours. fume.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe fume. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Styrene (100-42-5)		
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	1080 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	250 ppm
methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate (80-62-6)		
EU	Local name	Methyl methacrylate
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (ppm)	100 ppm
ethanediol, ethylene glycol (107-21-1)		
EU	IOELV TWA (mg/m <sup>3</sup> )	246 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	492 mg/m <sup>3</sup>

# CLEARPOL EXTRA CLEAR ISO NPG POLYESTER GELCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethanediol, ethylene glycol (107-21-1)		
EU	IOELV STEL (ppm)	100 ppm

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### Hand protection:

Chemical resistant gloves (according to European standard NF EN 374 or equivalent). Protective gloves made of PVC. neoprene gloves. Nitrile rubber gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Wear appropriate mask

Device	Filter type	Condition	Standard
	Type A - High-boiling (>65 °C) organic compounds		



#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: - 31 °C (Styrene)
Freezing point	: No data available
Boiling point	: 145 °C (Styrene)
Flash point	: 31 °C (Styrene)
Auto-ignition temperature	: 490 °C (Styrene)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 1,08 - 1,12
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 1.1 %(V) (Styrene)
Upper explosive limit (UEL)	: 6.1 %(V) (Styrene)

# CLEARPOL EXTRA CLEAR ISO NPG POLYESTER GELCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Inhalation:dust,mist: Harmful if inhaled.

ATE CLP (dust,mist)	3,6666943543 mg/l/4h
---------------------	----------------------

Styrene (100-42-5)	
LD50 oral	> 5000 mg/kg
LD50 dermal	> 5000 mg/kg

methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate (80-62-6)	
LD50 oral rat	7872 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat (mg/l)	29,8 mg/l/4h

ethanediol, ethylene glycol (107-21-1)	
LD50 oral rat	7712 mg/kg
LD50 dermal	> 3500 mg/kg mouse
LC50 inhalation rat (mg/l)	> 2,5 mg/l 6 h

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : May cause genetic defects.  
Carcinogenicity : May cause cancer.  
Reproductive toxicity : Suspected of damaging fertility or the unborn child.  
  
STOT-single exposure : Not classified  
STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.  
Aspiration hazard : Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.  
Acute aquatic toxicity : Not classified  
Chronic aquatic toxicity : Not classified

Styrene (100-42-5)	
LC50 fish 1	4,02 mg/l (96 h) (Pimephales promelas)
EC50 Daphnia 1	4,7 mg/l (48 h) (Daphnia magna)

# CLEARPOL EXTRA CLEAR ISO NPG POLYESTER GELCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Styrene (100-42-5)</b>	
EC50 72h algae (1)	4,9 mg/l (Pseudokirchneriella subcapitata)
<b>methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate (80-62-6)</b>	
LC50 fish 1	130 mg/l (Pimephales promelas)
EC50 Daphnia 1	69 mg/l (daphnia magna; 48h)
EC50 96h algae (1)	170 mg/l (selenastrum capricornutum)
<b>ethanediol, ethylene glycol (107-21-1)</b>	
LC50 fish 1	72860 mg/l Pimephales promelas
EC50 Daphnia 1	> 100 mg/l Daphnia magna, 48 h
EC50 96h algae (1)	6500 - 13000 mg/l Selenastrum capricornutum
NOEC chronic fish	15380 mg/l Pimephales Promelas
NOEC chronic crustacea	8590 mg/l Ceriodaphnia Dubia

### 12.2. Persistence and degradability

<b>ethanediol, ethylene glycol (107-21-1)</b>	
Biodegradation	90 - 100 %

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available




## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Additional information : Flammable vapours may accumulate in the container.

## SECTION 14: Transport information

In accordance with ADR / IATA / IMDG

ADR	IMDG	IATA
14.1. UN number		
1866	1866	1866
14.2. UN proper shipping name		
RESIN SOLUTION	RESIN SOLUTION	Resin solution
Transport document description		
UN 1866 RESIN SOLUTION, 3, III, (D/E)	UN 1866 RESIN SOLUTION, 3, III	UN 1866 Resin solution, 3, III
14.3. Transport hazard class(es)		
3	3	3
		
14.4. Packing group		
III	III	III
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		

### 14.6. Special precautions for user

#### - Overland transport

Special provisions (ADR) : 640E  
Transport category (ADR) : 3  
Hazard identification number (Kemler No.) : 30

# CLEARPOL EXTRA CLEAR ISO NPG POLYESTER GELCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Orange plates : 

30
1866

Tunnel restriction code (ADR) : D/E  
EAC code : •3YE

### - Transport by sea

EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-E  
Stowage category (IMDG) : A  
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

### - Air transport

PCA packing instructions (IATA) : 355  
CAO packing instructions (IATA) : 366  
ERG code (IATA) : 3L

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions  
Contains no substance on the REACH candidate list  
Contains no REACH Annex XIV substances

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Indication of changes:

Section	Changed item	Change	Comments

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 1B	Germ cell mutagenicity, Category 1B
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation

# CLEARPOL EXTRA CLEAR ISO NPG POLYESTER GELCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H340	May cause genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H361d	Suspected of damaging the unborn child
H372	Causes damage to organs through prolonged or repeated exposure

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 3	H226	Expert judgment
Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Muta. 1B	H340	Calculation method
Carc. 1B	H350	Calculation method
Repr. 2	H361	Calculation method
STOT RE 1	H372	Calculation method

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*