

CULR™ Art Pigment for Epoxy – Polished Copper

Revision date: 10.03.2023

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier CULR™ Art Pigment for Epoxy – Polished Copper

UFI: N58H-09H4-E20J-VJP9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Paints and varnishes

1.3. Details of the supplier of the safety data sheet

Company name: Easy Composites Ltd
Street: Unit 39 Park Hall Business Village
Place: Stoke on Trent, ST3 5XA.
United Kingdom.
Telephone: +44 (0)1782 4544499
E-mail: technical@glasscastresin.com

1.4. Emergency telephone number: Emergency CONTACT (Office Hours) Phone: +44 (0)1782 4544499

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

maleic anhydride

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Signal word: Warning

Pictograms:



Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SAFETY DATA SHEET

in acc. with Regulation (EU) No. 2015/830

CULR™ Art Pigment for Epoxy – Polished Copper

Revision date: 10.03.2023

Page 2 of 12

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
	Polyaminamidsalz (72243/00/2008.0023, Germany)			5 - < 10 %
	Skin Irrit. 2; H315			
108-31-6	maleic anhydride			< 0.1 %
	203-571-6	607-096-00-9		
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Resp. Sens. 1, Skin Sens. 1A, STOT RE 1; H302 H314 H318 H334 H317 H372 EUH071			
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one			< 0.1 %
	220-120-9	613-088-00-6	01-2120761540-60	
	Acute Tox. 2, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 2; H330 H302 H315 H318 H317 H400 H411			
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)			< 0.1 %
	-	613-167-00-5	01-2120764691-48	
	Acute Tox. 2, Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H310 H301 H314 H318 H317 H400 H410 EUH071			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
108-31-6	203-571-6	maleic anhydride	< 0.1 %
		oral: ATE = 500 mg/kg Skin Sens. 1A; H317: >= 0,001 - 100	
2634-33-5	220-120-9	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	< 0.1 %
		inhalation: ATE = 0,5 mg/l (vapours); inhalation: LC50 = 0,5 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 670 - 784 mg/kg Skin Sens. 1; H317: >= 0,05 - 100	
55965-84-9	-	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	< 0.1 %
		inhalation: ATE = 0,5 mg/l (vapours); inhalation: LC50 = 0,171 mg/l (dusts or mists); dermal: LD50 = 92,4 mg/kg; oral: LD50 = 64 mg/kg Skin Corr. 1C; H314: >= 0,6 - 100 Skin Irrit. 2; H315: >= 0,06 - < 0,6 Eye Dam. 1; H318: >= 0,6 - 100 Eye Irrit. 2; H319: >= 0,06 - < 0,6 Skin Sens. 1A; H317: >= 0,0015 - 100 Aquatic Acute 1; H400: M=100 Aquatic Chronic 1; H410: M=100	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice.

After inhalation

Provide fresh air. If unconscious but breathing normally, place in recovery position and seek medical advice. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.

CULR™ Art Pigment for Epoxy – Polished Copper

Revision date: 10.03.2023

Page 3 of 12

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. @0405.B004145 Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Non-flammable.

In case of fire may be liberated: Pyrolysis products, toxic

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment.

For emergency responders

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

For containment

Stop leak if safe to do so. Cover drains.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

CULR™ Art Pigment for Epoxy – Polished Copper

Revision date: 10.03.2023

Page 4 of 12

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation. Avoid contact with skin, eyes and clothes. Do not breathe dust/fume/gas/mist/vapours/spray. Use personal protection equipment.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Store in a well-ventilated place. Store in a dry place.

Hints on joint storage

No information available.

7.3. Specific end use(s)

Colour, Pigment

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
-	Dust, inhalable	-	10		TWA (8 h)	WEL
-	Dust, respirable	-	4		TWA (8 h)	WEL
108-31-6	Maleic anhydride	-	1		TWA (8 h)	WEL
		-	3		STEL (15 min)	WEL

SAFETY DATA SHEET

in acc. with Regulation (EU) No. 2015/830

CULR™ Art Pigment for Epoxy – Polished Copper

Revision date: 10.03.2023

Page 5 of 12

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
108-31-6	maleic anhydride			
Worker DNEL, acute		inhalation	systemic	0,8 mg/m ³
Worker DNEL, acute		inhalation	local	0,8 mg/m ³
Worker DNEL, long-term		inhalation	systemic	0,4 mg/m ³
Worker DNEL, long-term		inhalation	local	0,4 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,04 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	0,04 mg/kg bw/day
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one			
Worker DNEL, long-term		inhalation	systemic	6,81 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,966 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1,2 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,345 mg/kg bw/day
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)			
Worker DNEL, long-term		inhalation	local	0,02 mg/m ³
Worker DNEL, acute		inhalation	local	0,04 mg/m ³
Consumer DNEL, long-term		inhalation	local	0,02 mg/m ³
Consumer DNEL, acute		inhalation	local	0,04 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,09 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	0,11 mg/kg bw/day

SAFETY DATA SHEET

in acc. with Regulation (EU) No. 2015/830

CULR™ Art Pigment for Epoxy – Polished Copper

Revision date: 10.03.2023

Page 6 of 12

PNEC values

CAS No	Substance	Value
Environmental compartment		
108-31-6	maleic anhydride	
Freshwater		0,04281 mg/l
Freshwater (intermittent releases)		0,4281 mg/l
Marine water		0,004281 mg/l
Freshwater sediment		0,344 mg/kg
Marine sediment		0,0334 mg/kg
Micro-organisms in sewage treatment plants (STP)		44,6 mg/l
Soil		0,0415 mg/kg
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	
Freshwater		0,00403 mg/l
Freshwater (intermittent releases)		0,0011 mg/l
Marine water		0,000403 mg/l
Freshwater sediment		0,0499 mg/kg
Marine sediment		0,00499 mg/kg
Micro-organisms in sewage treatment plants (STP)		1,03 mg/l
Soil		3 mg/kg
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	
Freshwater		0,00339 mg/l
Freshwater (intermittent releases)		0,00339 mg/l
Marine water		0,00339 mg/l
Freshwater sediment		0,027 mg/kg
Marine sediment		0,027 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,23 mg/l
Soil		0,01 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Wear protective gloves.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

CULR™ Art Pigment for Epoxy – Polished Copper

Revision date: 10.03.2023

Page 7 of 12

Skin protection

Use of protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Thermal hazards

No information available.

Environmental exposure controls

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	Copper	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		100 °C
Flammability:		Non-flammable.
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		> 100 °C
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value:		6 - 8
Viscosity / kinematic:		not determined
Water solubility:	(Pigment) practically insoluble	
Solubility in other solvents		not determined
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		not determined
Density:		not determined
Relative vapour density:		not determined
Particle characteristics:		not applicable

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

CULR™ Art Pigment for Epoxy – Polished Copper

Revision date: 10.03.2023

Page 8 of 12

10.6. Hazardous decomposition products

In case of fire may be liberated: Pyrolysis products, toxic

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix:

oral: > 2000 mg/kg

dermal: > 2000 mg/kg

Inhalation (vapour): >20 mg/L (4 h)

Inhalation (dust/mist): > 5 mg/L (4h)

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
108-31-6	maleic anhydride				
	oral	ATE mg/kg	500		
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one				
	oral	LD50 mg/kg	670 - 784	Rat	Manufacturer OECD 401
	dermal	LD50 mg/kg	> 2000	Rat	Manufacturer OECD 402
	inhalation vapour	ATE	0,5 mg/l		
	inhalation (4 h) dust/mist	LC50	0,5 mg/l	Rat	Manufacturer OPPTS 870.1300
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)				
	oral	LD50	64 mg/kg	Rat	Manufacturer
	dermal	LD50 mg/kg	92,4	Rabbit	Manufacturer
	inhalation vapour	ATE	0,5 mg/l		
	inhalation (4 h) dust/mist	LC50	0,171 mg/l	Rat	Manufacturer OECD 403

Irritation and corrosivity

Based on available data, the classification criteria are not met.

In case of skin contact: slightly irritant but not relevant for classification.

Sensitising effects

May cause an allergic skin reaction. (maleic anhydride; 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one; reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1))

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

Skin contact, Eye contact, @ES04.B002063, Inhalation.

SAFETY DATA SHEET

in acc. with Regulation (EU) No. 2015/830

CULR™ Art Pigment for Epoxy – Polished Copper

Revision date: 10.03.2023

Page 9 of 12

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.
The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one					
	Acute algae toxicity	ErC50 mg/l	0,110	72 h	Selenastrum capricornutum	Manufacturer OECD 201
	Acute crustacea toxicity	EC50 mg/l	0,643	48 h	Daphnia magna (Big water flea)	Manufacturer OECD 202
	Fish toxicity	NOEC mg/l	0,21	28 d	Oncorhynchus mykiss (Rainbow trout)	Manufacturer OECD 215
	Crustacea toxicity	NOEC mg/l	0,25	4 d	Mysidopsis bahia	Manufacturer
	Acute bacteria toxicity	(EC50 mg/l)	23	3 h	Activated sludge	Manufacturer OECD 209
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)					
	Acute algae toxicity	ErC50 mg/l	0,0052	72 h	Skeletonema costatum	Manufacturer OECD 201
	Acute bacteria toxicity	(EC50 mg/l)	7,92	3 h	Activated sludge	Manufacturer OECD 209

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one			
	OECD 301C	85 %	63	Manufacturer
	Moderately/partially biodegradable.			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	-0,71 - 0,75

BCF

CAS No	Chemical name	BCF	Species	Source
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	6,62	Lepomis macrochirus (Bluegill)	Manufacturer
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	3,6		Manufacturer

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

CULR[™] Art Pigment for Epoxy – Polished Copper

Revision date: 10.03.2023

Page 10 of 12

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

CULR™ Art Pigment for Epoxy – Polished Copper

Revision date: 10.03.2023

Page 11 of 12

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

2004/42/EC (VOC): < 1 %

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

LL50: Lethal loading, 50%

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules

MFAG: Medical First Aid Guide

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

VOC: Volatile Organic Compounds

SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

SAFETY DATA SHEET

in acc. with Regulation (EU) No. 2015/830

CULR™ Art Pigment for Epoxy – Polished Copper

Revision date: 10.03.2023

Page 12 of 12

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)