



SAFETY DATA SHEET

EG160 High Temp Epoxy Tooling Gelcoat

Page: 1

Compilation date: 24/05/2017

Revision date: 21/08/2018

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: EG160 High Temp Epoxy Tooling Gelcoat

Product code: EP-G160

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants. PC9a: Coatings and paints, thinners, paint removers. PC9b: Fillers, putties, plasters, modelling clay. PC32: Polymer preparations and compounds. PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring PROC19: Hand-mixing with intimate contact and only PPE available ERC2: Formulation of preparations* ERC3: Formulation in materials ERC5: Industrial use resulting in inclusion into or onto a matrix ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

1.3. Details of the supplier of the safety data sheet

Company name: Easy Composites Ltd
Unit 39, Park Hall Business Village
Longton, Stoke on Trent
Staffordshire
ST3 5XA
United Kingdom

Tel: +44 (0) 1782 454499

Email: sales@easycomposites.co.uk

SAFETY DATA SHEET

EG160 High Temp Epoxy Tooling Gelcoat

Page: 2

1.4. Emergency telephone number

Emergency tel: +44 (0) 1782 454499
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411; Repr. 1B: H360F; Skin Corr. 1C: H314; Skin Sens. 1: H317

Most important adverse effects: Causes severe skin burns and eye damage. May cause an allergic skin reaction. May damage fertility. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.
H317: May cause an allergic skin reaction.
H360F: May damage fertility.
H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS05: Corrosion
GHS07: Exclamation mark
GHS08: Health hazard
GHS09: Environmental



Signal words: Danger

Precautionary statements: P260: Do not breathe dust/fume/gas/mist/vapours/spray.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P302+P352: IF ON SKIN: Wash with plenty of water.
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P362+P364: Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

[cont...]

SAFETY DATA SHEET

EG160 High Temp Epoxy Tooling Gelcoat

Page: 3

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT} - REACH registered number(s): 01-2119456619-26

EINECS	CAS	PBT / WEL	CLP Classification	Percent
500-033-5	25068-38-6	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	1-25%

1,3-PROPANEDIOL, 2,2-BIS(HYDROXYMETHYL)-, POLYMER WITH 2-(CHLOROMETHYL)OXIRANE

608-564-5	30973-88-7	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1: H317	1-25%
-----------	------------	---	--	-------

N,N,N',N'-TETRAGLYCIDYL-4,4'-DIAMINO DIPHENYL METHANE

249-204-3	28768-32-3	-	Aquatic Chronic 2: H411; Skin Sens. 1: H317	1-25%
-----------	------------	---	--	-------

1,3-PROPANEDIOL, 2-ETHYL-2-(HYDROXYMETHYL)-, POLYMER WITH (CHLOROMETHYL)OXIRANE -
TRIMETHYLOLPROPANE TRIGLYCIDYLETHER - REACH registered number(s): 01-2120078341-60

608-489-8	30499-70-8	-	Skin Corr. 1C: H314; Repr. 1B: H360F; Aquatic Chronic 2: H411; Eye Dam. 1: H318; Skin Sens. 1B: H317	1-25%
-----------	------------	---	--	-------

PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER

-	28064-14-4	-	Skin Irrit. 2: H315; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Sens. 1: H317	1-25%
---	------------	---	--	-------

N,N-DIGLYCIDYL ANILINE

-	2095-06-9	-	Acute Tox. 4: H302; Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; STOT SE 3: H335	1-25%
---	-----------	---	--	-------

Section 4: First aid measures

4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.
- Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
- Ingestion:** Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

[cont...]

SAFETY DATA SHEET

EG160 High Temp Epoxy Tooling Gelcoat

Page: 4

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid. Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

[cont...]

SAFETY DATA SHEET

EG160 High Temp Epoxy Tooling Gelcoat

Page: 5

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Environmental: The floor of the storage room must be impermeable to prevent the escape of liquids.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Grey

Odour: Characteristic odour

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: No data available.

Viscosity: Highly viscous

Boiling point/range°C: No data available.

Flammability limits %: lower: No data available.

Flash point°C: No data available.

Autoflammability°C: No data available.

Melting point/range°C: No data available.

upper: No data available.

Part.coeff. n-octanol/water: No data available.

[cont...]

SAFETY DATA SHEET

EG160 High Temp Epoxy Tooling Gelcoat

Page: 6

Relative density: 1.13 - 1.18

VOC g/l: No data available.

Vapour pressure: No data available.

pH: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

N,N,N',N'-TETRAGLYCIDYL-4,4'-DIAMINO DIPHENYL METHANE

DERMAL	RBT	LD50	>3000	mg/kg
DUST/MIST	RAT	4H LC50	>30	mg/m3
ORAL	MUS	LD50	>5000	mg/kg

[cont...]

SAFETY DATA SHEET

EG160 High Temp Epoxy Tooling Gelcoat

Page: 7

1,3-PROPANEDIOL, 2-ETHYL-2-(HYDROXYMETHYL)-, POLYMER WITH (CHLOROMETHYL)OXIRANE - TRIMETHYLOLPROPANE TRIGLYCIDYLETHER

DERMAL	RAT	LD50	> 3170	mg/kg
--------	-----	------	--------	-------

PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2001	mg/kg
VAPOURS	RAT	5H LC0	0.00001	ppm

N,N-DIGLYCIDYL ANILINE

DERMAL	RBT	LD50	3560	mg/kg
ORAL	RAT	LD50	>1620	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
Reproductive toxicity	--	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

1,3-PROPANEDIOL, 2,2-BIS(HYDROXYMETHYL)-, POLYMER WITH 2-(CHLOROMETHYL)OXIRANE

Golden Orfe (Leuciscus idus)	96H LC50	460	mg/l
------------------------------	----------	-----	------

N,N,N',N'-TETRAGLYCIDYL-4,4'-DIAMINO DIPHENYL METHANE

ALGAE	96H ErC50	38.234	mg/l
-------	-----------	--------	------

[cont...]

SAFETY DATA SHEET

EG160 High Temp Epoxy Tooling Gelcoat

Page: 8

CRUSTACEA	48h LC50	14.682	mg/l
FISH	96H LC50	2.454	mg/l

1,3-PROPANEDIOL, 2-ETHYL-2-(HYDROXYMETHYL)-, POLYMER WITH (CHLOROMETHYL)OXIRANE - TRIMETHYLOLPROPANE TR

Daphnia magna	48H EC50	3.7	mg/l
FISH	96H LC50	75	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H ErC50	9	mg/l

PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER

ALGAE	72H EC50	9.4	mg/l
BACTERIA	3H IC50	>100	mg/l
DAPHNIA	21D Semi Static NOEC	0.3	mg/l
DAPHNIA	48H EC50	1.7	mg/l
FISH	96H LC50	1.5	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1760

[cont...]

SAFETY DATA SHEET

EG160 High Temp Epoxy Tooling Gelcoat

Page: 9

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, N.O.S.
(1,3-PROPANEDIOL, 2-ETHYL-2-(HYDROXYMETHYL)-, POLYMER WITH
(CHLOROMETHYL)OXIRANE - TRIMETHYLOLPROPANE TRIGLYCIDYLETHER)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.
H314: Causes severe skin burns and eye damage.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H319: Causes serious eye irritation.
H335: May cause respiratory irritation.
H360F: May damage fertility.
H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

[cont...]

SAFETY DATA SHEET

EG160 High Temp Epoxy Tooling Gelcoat

Page: 10

and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: EG160 High Temp Epoxy Tooling Gelcoat Hardener

Product code: EP-G160

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants. PC9a: Coatings and paints, thinners, paint removers. PC9b: Fillers, putties, plasters, modelling clay. PC32: Polymer preparations and compounds. PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring PROC19: Hand-mixing with intimate contact and only PPE available ERC2: Formulation of preparations* ERC3: Formulation in materials ERC5: Industrial use resulting in inclusion into or onto a matrix ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

1.3. Details of the supplier of the safety data sheet

Company name: Easy Composites Ltd
Unit 39, Park Hall Business Village
Longton, Stoke on Trent
Staffordshire
ST3 5XA
United Kingdom
Tel: +44 (0) 1782 454499
Fax: +44 (0) 1782 596868
Email: sales@easycomposites.co.uk

SAFETY DATA SHEET

EG160 High Temp Epoxy Tooling
Gelcoat Hardener

Page: 2

1.4. Emergency telephone number

Emergency tel: +44 (0) 1782 454499
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1B: H314; Skin Sens. 1: H317; STOT RE 2: H373; Acute Tox. 4: H302; Aquatic Chronic 2: H411; -: EUH208

Most important adverse effects: Contains 3,6-diazaoctanethylenediamine. May produce an allergic reaction. Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains 3,6-diazaoctanethylenediamine. May produce an allergic reaction.
H302: Harmful if swallowed.
H314: Causes severe skin burns and eye damage.
H317: May cause an allergic skin reaction.
H373: May cause damage to organs through prolonged or repeated exposure.
H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS05: Corrosion
GHS07: Exclamation mark
GHS08: Health hazard
GHS09: Environmental



Signal words: Danger

Precautionary statements: P260: Do not breathe dust/fumes/gas/mist/vapours/spray.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P301+312: IF SWALLOWED: Call a if you feel unwell.
P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P302+352: IF ON SKIN: Wash with plenty of water/.
P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.
Rinse skin with water.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

[cont...]

SAFETY DATA SHEET

EG160 High Temp Epoxy Tooling
Gelcoat Hardener

Page: 3

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE - REACH registered number(s): 01-2119514687-32

EINECS	CAS	PBT / WEL	CLP Classification	Percent
220-666-8	2855-13-2	-	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 3: H412	25-50%

4,4 METHYLENEBIS (CYCLOHEXYLAMINE) - REACH registered number(s): 01-2119541673-38

217-168-8	1761-71-3	-	Acute Tox. 4: H302; Skin Corr. 1B: H314; STOT RE 2: H373; Eye Dam. 1: H318; Skin Sens. 1: H317	25-50%
-----------	-----------	---	--	--------

2-ETHYL-4-METHYLIMIDAZOLE

213-234-5	931-36-2	-	Acute Tox. 4: H302; Eye Dam. 1: H318	25-50%
-----------	----------	---	--------------------------------------	--------

FATTY ACIDS, C-18 UNSATD, TRIMERS, REACTION PRODUCT WITH TRIETHYLENE TETRAMINE

605-297-6	162627-18-1	-	Skin Sens. 1B: H317; Aquatic Acute 1: H400; Aquatic Chronic 1: H410	1-25%
-----------	-------------	---	--	-------

3,6-DIAZAOCTANETHYLENEDIAMINE - REACH registered number(s): 01-2119487919-13

203-950-6	112-24-3	-	Acute Tox. 4: H312; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 3: H412	0.05-1%
-----------	----------	---	--	---------

Section 4: First aid measures

4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.
Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.
- Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
- Ingestion:** Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water to drink immediately. Transfer to hospital as soon as possible.
- Inhalation:** Move to fresh air in case of accidental inhalation of vapours. Remove casualty from exposure ensuring one's own safety whilst doing so. If conscious, ensure the casualty sits or lies down. If unconscious, check for breathing and apply artificial respiration if necessary. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

- Skin contact:** Severe burns may occur. There may be irritation and redness at the site of contact.
- Eye contact:** There may be severe pain. Corneal burns may occur. May cause permanent damage.

[cont...]

SAFETY DATA SHEET

EG160 High Temp Epoxy Tooling
Gelcoat Hardener

Page: 4

Ingestion: Corrosive burns may appear around the lips. There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Show this safety data sheet to the doctor in attendance.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Dry chemical powder. Alcohol or polymer foam. Water spray. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear protective clothing to prevent contact with skin and eyes. Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Mix with sand or vermiculite. Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

[cont...]

SAFETY DATA SHEET

EG160 High Temp Epoxy Tooling
Gelcoat Hardener

Page: 5

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Keep container tightly closed. Avoid incompatible materials and conditions - see section 10 of SDS.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

Hazardous ingredients:

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	20.1 mg/m ³	Workers	-
PNEC	Fresh water	0.06 mg/l	-	-
PNEC	Marine water	0.006 mg/l	-	-

3,6-DIAZAOCTANETHYLENEDIAMINE

Type	Exposure	Value	Population	Effect
DNEL	Dermal	0.57 mg/kg	Workers	Systemic
DNEL	Inhalation	1 mg/m ³	Workers	Local
DNEL	Dermal	0.25 mg/kg	Consumers	Systemic
DNEL	Oral	0.41 mg/kg	Consumers	Systemic
DNEL	Inhalation	0.29 mg/m ³	Consumers	Systemic
PNEC	Fresh water	0.19 mg/l	-	-
PNEC	Marine water	0.038 mg/l	-	-
PNEC	Fresh water sediments	95.9 mg/kg	-	-
PNEC	Marine sediments	19.2 mg/kg	-	-
PNEC	Soil (agricultural)	19.1 mg/kg	-	-
PNEC	Microorganisms in sewage treatment	4.25 mg/l	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Gas/vapour filter, type K: ammonia and derivatives (EN141).

Hand protection: Impermeable gloves.

Eye protection: Safety glasses with side-shields. Ensure eye bath is to hand.

[cont...]

SAFETY DATA SHEET

EG160 High Temp Epoxy Tooling
Gelcoat Hardener

Page: 6

Skin protection: Impermeable protective clothing.

Environmental: Ensure all engineering measures mentioned in section 7 of SDS are in place.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow-orange

Odour: Characteristic odour

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: No data available.

Viscosity: 130 mPas (25°C)

Boiling point/range°C: No data available.

Flammability limits %: lower: No data available.

Flash point°C: No data available.

Autoflammability°C: No data available.

Relative density: 0.92 - 0.97

VOC g/l: No data available.

Melting point/range°C: No data available.

upper: No data available.

Part.coeff. n-octanol/water: No data available.

Vapour pressure: No data available.

pH: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may generate enough heat and gases for fires/explosions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Sources of ignition.

10.5. Incompatible materials

Materials to avoid: Acids. Oxidising agents. Metals.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

[cont...]

SAFETY DATA SHEET

EG160 High Temp Epoxy Tooling
Gelcoat Hardener

Page: 7

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

DERMAL	RBT	LD50	1840	mg/kg
ORAL	RAT	LD50	1030	mg/kg

4,4 METHYLENEBIS (CYCLOHEXYLAMINE)

DERMAL	RBT	LD50	2110	mg/kg
ORAL	RAT	LD50	625	mg/kg

2-ETHYL-4-METHYLIMIDAZOLE

ORAL	RAT	LD50	622	mg/kg
------	-----	------	-----	-------

3,6-DIAZAOCTANETHYLENEDIAMINE

IVN	MUS	LD50	350	mg/kg
ORL	MUS	LD50	1600	mg/kg
ORL	RAT	LD50	2500	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	ING	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Severe burns may occur. There may be irritation and redness at the site of contact.

Eye contact: There may be severe pain. Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

[cont...]

SAFETY DATA SHEET

EG160 High Temp Epoxy Tooling
Gelcoat Hardener

Page: 8

12.1. Toxicity

Hazardous ingredients:

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

BACTERIA	15H EC10	1120	mg/l
Daphnia magna	48H EC50	23	mg/l
Scenedesmus Subspicatus	72H EC50	> 50	mg/l
ZEBRAFISH (Brachydanio rerio)	96H LC50	110	mg/l

4,4 METHYLENEBIS (CYCLOHEXYLAMINE)

Daphnia magna	48H EC50	6.84	mg/l
Daphnia magna	504H NOEC	4	mg/l
GOLDEN ORFE (Leuciscus idus)	96H LC50	46 - 100	mg/l

2-ETHYL-4-METHYLIMIDAZOLE

Daphnia magna	48H EC50	30	mg/l
FISH	96H LD50	46 - 100	mg/l

3,6-DIAZAOCTANETHYLENEDIAMINE

Daphnia magna	48H EC50	10 - 100	mg/l
FATHEAD MINNOW (Pimephales promelas)	96H LC50	> 100	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H ErC50	10 - 100	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Arrange for collection by specialised disposal company.

[cont...]

SAFETY DATA SHEET

EG160 High Temp Epoxy Tooling
Gelcoat Hardener

Page: 9

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN2735

14.2. UN proper shipping name

Shipping name: POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(Contains: Aliphatic Amines; FATTY ACIDS, C-18 UNSATD, TRIMERS, REACTION PRODUCT WITH TRIETHYLENE TETRAMINE)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Tunnel code: E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

[cont...]

SAFETY DATA SHEET

EG160 High Temp Epoxy Tooling
Gelcoat Hardener

Page: 10

H318: Causes serious eye damage.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.