



# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

GHS08

Signal word (CLP)

: Danger

Contains

: Styrene; Cobalt bis(2-ethylhexanoate)

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H332 - Harmful if inhaled.  
H335 - May cause respiratory irritation.  
H361 - Suspected of damaging fertility or the unborn child.  
H372 - Causes damage to organs through prolonged or repeated exposure.  
H412 - Harmful to aquatic life with long lasting effects.  
Precautionary statements (CLP) : P280 - Wear protective gloves, protective clothing, eye protection.  
P241 - Use explosion-proof electrical equipment.  
P271 - Use only outdoors or in a well-ventilated area.  
P370+P378 - In case of fire: Use Water fog, foam, extinguishing powder, carbon dioxide (CO2) for extinction.  
P264 - Wash hands thoroughly after handling.  
P210 - Keep away from heat, hot surfaces, sparks, open flames. — No smoking.

### 2.3. Other hazards

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Styrene	CAS-No.: 100-42-5 EC-No.: 202-851-5 EC Index-No.: 601-026-00-0 REACH-no: 01-2119457861-32	40 – 60	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361d STOT SE 3, H335 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Naphtha (petroleum), hydrodesulfurized heavy substance with a Community workplace exposure limit	CAS-No.: 64742-82-1 EC-No.: 265-185-4 EC Index-No.: 649-330-00-2 REACH-no: 01-2119458049-33	0,1 – 0,5	STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Flam. Liq. 3, H226 Muta. Not classified Carc. Not classified STOT RE Not classified
Cobalt bis(2-ethylhexanoate)	CAS-No.: 136-52-7 EC-No.: 205-250-6 REACH-no: 01-2119524678-29	0,1 – 0,2	Eye Irrit. 2, H319 Skin Sens. 1A, H317 Repr. 1B, H360F Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Hydrotreated Heavy naphtha - benzene <0.1% substance with a Community workplace exposure limit	CAS-No.: 64742-48-9 EC-No.: 265-150-3 EC Index-No.: 649-327-00-6 REACH-no: 01-2119463258-33	0,01 – 0,2	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304
MONOETHYLENE GLYCOL substance with a Community workplace exposure limit	CAS-No.: 107-21-1 EC-No.: 203-473-3 EC Index-No.: 603-027-00-1 REACH-no: 01-2119472426-35	0,1 – 0,2	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg de poids corporel) STOT RE 2, H373
propionic acid ... % substance with a Community workplace exposure limit	CAS-No.: 79-09-4 EC-No.: 201-176-3 EC Index-No.: 607-089-00-0 REACH-no: 01-2119486971-24	< 0,01	Flam. Liq. 3, H226 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334

### Specific concentration limits

Name	Product identifier	Specific concentration limits
propionic acid ... %	CAS-No.: 79-09-4 EC-No.: 201-176-3 EC Index-No.: 607-089-00-0 REACH-no: 01-2119486971-24	( 10 ≤C < 25) Skin Irrit. 2, H315 ( 10 ≤C < 25) Eye Irrit. 2, H319 ( 10 ≤C ≤ 100) STOT SE 3, H335 ( 25 ≤C ≤ 100) Skin Corr. 1B, H314

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Irritation.  
Symptoms/effects after eye contact : Eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Use water spray or fog for cooling exposed containers. Prevent entry to sewers and public waters.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Do not breathe vapours. fume.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe fume. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.  
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1. National occupational exposure and biological limit values

Styrene (100-42-5)	
<b>Austria - Occupational Exposure Limits</b>	
Local name	Styrol
MAK (OEL TWA)	85 mg/m <sup>3</sup>
MAK (OEL TWA) [ppm]	20 ppm
MAK (OEL STEL)	340 mg/m <sup>3</sup> (4x 15(Miw) min)
MAK (OEL STEL) [ppm]	80 ppm (4x 15(Miw) min)
Remark (AT)	Fortpflanzungsgefährdend: d
Regulatory reference	BGBl. II Nr. 382/2020
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Styrène (monomère) # Styreen (monomeer)
OEL TWA	108 mg/m <sup>3</sup>
OEL TWA [ppm]	25 ppm
OEL STEL	216 mg/m <sup>3</sup>
OEL STEL [ppm]	50 ppm
Remark (BE)	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020
<b>Czech Republic - Occupational Exposure Limits</b>	
Local name	Styren (Ethenylbenzen; Fenylethylen; Vinylbenzen)
PEL (OEL TWA)	100 mg/m <sup>3</sup>
PEL (OEL TWA) [ppm]	23 ppm
NPK-P (OEL C)	400 mg/m <sup>3</sup>
NPK-P (OEL C) [ppm]	92 ppm
Remark (CZ)	B - u látky je zaveden biologický expoziční test (BET) v moči nebo krvi, I - dráždí sliznice (oči, dýchací cesty), respektive kůže, P - u látky nelze vyloučit závažné pozdní účinky (s větou H372, H373).

# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>Styrene (100-42-5)</b>	
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 41/2020 Sb.)
<b>Czech Republic - Biological limit values</b>	
Local name	Styren (Ethenylbenzen; Fenylethylen; Vinylbenzen)
BLV	400 mg/g creatinine Ukazatel: Mandlová kyselina - Biološki uzorak: moči - Doba odběru: konec směny 300 µmol/mmol Creatinine Ukazatel: Mandlová kyselina - Biološki uzorak: moči - Doba odběru: konec směny 600 mg/g creatinine Ukazatel: Mandlová + fenylglyoxylová kyselina - Biološki uzorak: moči - Doba odběru: konec směny
Regulatory reference	Vyhláška č. 107/2013 Sb. (kterou se mění vyhláška č. 432/2003 Sb.)
<b>Estonia - Occupational Exposure Limits</b>	
Local name	Stüreen (fenüületeen, vinüülbenseen)
OEL TWA	90 mg/m <sup>3</sup>
OEL TWA [ppm]	20 ppm
OEL STEL	200 mg/m <sup>3</sup>
OEL STEL [ppm]	50 ppm
Remark (ET)	A (Naha kaudu kergesti imenduv aine)
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 17.10.2019, 2); Vabariigi Valitsuse 10. märtsi 2019. a määruse nr 84
<b>Finland - Occupational Exposure Limits</b>	
Local name	Styreeni
HTP (OEL TWA) [1]	86 mg/m <sup>3</sup>
HTP (OEL TWA) [2]	20 ppm
HTP (OEL STEL)	430 mg/m <sup>3</sup>
HTP (OEL STEL) [ppm]	100 ppm
Huomautus (FI)	Melu
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
<b>Finland - Biological limit values</b>	
Local name	Styreeni
BLV	1,2 mmol/l Parametri: Virtsan MAPGA (Virtsan manteli- ja fenyyli glykossyylihappo) - Näytteenottoajankohta: Työpäivän jälkeinen aamu
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
<b>Greece - Occupational Exposure Limits</b>	
Local name	Στυρόλιο
OEL TWA	425 mg/m <sup>3</sup>
OEL TWA [ppm]	100 ppm
OEL STEL	1050 mg/m <sup>3</sup>
OEL STEL [ppm]	250 ppm
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
<b>Romania - Occupational Exposure Limits</b>	
Local name	Stiren

# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>Styrene (100-42-5)</b>	
OEL TWA	50 mg/m <sup>3</sup>
OEL TWA [ppm]	12 ppm
OEL STEL	150 mg/m <sup>3</sup>
OEL STEL [ppm]	35 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 157/2020)
<b>Romania - Biological limit values</b>	
Local name	Stiren
BLV	800 mg/g creatinine Indicator biologic: Acid mandelic - Material biologic: urină - Momentul recoltării: sfârșit schimb 300 mg/g creatinine Indicator biologic: Acid mandelic - Material biologic: urină - Momentul recoltării: începutul schimbului următor 100 mg/g creatinine Indicator biologic: Acid fenilgioxalic - Material biologic: urină - Momentul recoltării: sfârșit schimb 0,55 mg/l Indicator biologic: Stiren - Material biologic: sânge - Momentul recoltării: sfârșit schimb 0,02 mg/l Indicator biologic: Stiren - Material biologic: sânge - Momentul recoltării: începutul schimbului următor
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 584/2018)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Styrene
WEL TWA (OEL TWA) [1]	430 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	100 ppm
WEL STEL (OEL STEL)	1080 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	250 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>MONOETHYLENE GLYCOL (107-21-1)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
IOEL TWA	246 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm
IOEL STEL	492 mg/m <sup>3</sup>
IOEL STEL [ppm]	100 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>Austria - Occupational Exposure Limits</b>	
Local name	Ethylenglykol (Ethandiol; Glykol)
MAK (OEL TWA)	26 mg/m <sup>3</sup>
MAK (OEL TWA) [ppm]	10 ppm
MAK (OEL STEL)	52 mg/m <sup>3</sup> (8x 5(Mow) min)
MAK (OEL STEL) [ppm]	20 ppm (8x 5(Mow) min)
Remark (AT)	H
Regulatory reference	BGBI. II Nr. 382/2020

# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

MONOETHYLENE GLYCOL (107-21-1)	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Ethylèneglycol (en aérosol) # Ethyleenglycol
OEL TWA	52 mg/m <sup>3</sup>
OEL TWA [ppm]	20 ppm
OEL STEL	104 mg/m <sup>3</sup>
OEL STEL [ppm]	40 ppm
Remark (BE)	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air, M: la mention "M" indique que lors d'une exposition supérieure à la valeur limite, des irritations apparaissent ou un danger d'intoxication aiguë existe. Le procédé de travail doit être conçu de telle façon que l'exposition ne dépasse jamais la valeur limite. Lors des mesurages, la période d'échantillonnage doit être aussi courte que possible afin de pouvoir effectuer des mesurages fiables. Le résultat des mesurages est calculé en fonction de la période d'échantillonnage. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht, M: de vermelding "M" duidt aan dat bij de blootstelling boven de grenswaarde irritatie optreedt of er gevaar bestaat voor acute vergiftiging. Het werkproces moet zo zijn ontworpen dat de blootstelling de grenswaarde nooit overschrijdt. Bij een controle geldt dat de bemonsterde periode zo kort mogelijk moet zijn om een betrouwbare meting te kunnen verrichten. Het meetresultaat wordt dan gerelateerd aan de beschouwde periode.
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020
<b>Czech Republic - Occupational Exposure Limits</b>	
Local name	Ethylenglykol (Ethan-1,2-diol)
PEL (OEL TWA)	50 mg/m <sup>3</sup>
PEL (OEL TWA) [ppm]	20 ppm
NPK-P (OEL C)	100 mg/m <sup>3</sup>
NPK-P (OEL C) [ppm]	39 ppm
Remark (CZ)	D - při expozici se významně uplatňuje pronikání faktoru kůží.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 41/2020 Sb.)
<b>Estonia - Occupational Exposure Limits</b>	
Local name	1,2-etaandiool (etüleenglükool)
OEL TWA	52 mg/m <sup>3</sup>
OEL TWA [ppm]	20 ppm
OEL STEL	104 mg/m <sup>3</sup>
OEL STEL [ppm]	40 ppm
Remark (ET)	A (Naha kaudu kergesti imenduv aine), 18 (Piirnorm kehtib auru ja aerosooli summaarse sisalduse kohta)
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 17.10.2019, 2); Vabariigi Valitsuse 10. märtsi 2019. a määruse nr 84
<b>Finland - Occupational Exposure Limits</b>	
Local name	1,2-Etaanidioli
HTP (OEL TWA) [1]	50 mg/m <sup>3</sup>
HTP (OEL TWA) [2]	20 ppm



# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>MONOETHYLENE GLYCOL (107-21-1)</b>	
HTP (OEL STEL)	100 mg/m <sup>3</sup>
HTP (OEL STEL) [ppm]	40 ppm
Huomautus (FI)	Iho
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
<b>Greece - Occupational Exposure Limits</b>	
Local name	Αιθυλενογλυκόλη (σπμοί)
OEL TWA	125 mg/m <sup>3</sup>
OEL TWA [ppm]	50 ppm
OEL STEL	125 mg/m <sup>3</sup>
OEL STEL [ppm]	50 ppm
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
<b>Italy - Occupational Exposure Limits</b>	
Local name	Etilen glicol
OEL TWA	52 mg/m <sup>3</sup>
OEL TWA [ppm]	20 ppm
OEL STEL	104 mg/m <sup>3</sup>
OEL STEL [ppm]	40 ppm
Notes	Cute
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
<b>Netherlands - Occupational Exposure Limits</b>	
Local name	Ethaan-1,2-diol
MAC-TGG (OEL TWA)	52 mg/m <sup>3</sup> (damp) 10 mg/m <sup>3</sup> (druppels)
MAC-15 (OEL STEL)	104 mg/m <sup>3</sup> (damp)
Remark (MAC)	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2020
<b>Romania - Occupational Exposure Limits</b>	
Local name	Etilenglicol/Etandiol
OEL TWA	52 mg/m <sup>3</sup>
OEL TWA [ppm]	20 ppm
OEL STEL	104 mg/m <sup>3</sup>
OEL STEL [ppm]	40 ppm
Remark	P - posibilitatea unei penetrări cutanate importante
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 157/2020)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Ethane-1,2-diol

# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>MONOETHYLENE GLYCOL (107-21-1)</b>	
WEL TWA (OEL TWA) [1]	10 mg/m <sup>3</sup> particulate 52 mg/m <sup>3</sup> vapour
WEL TWA (OEL TWA) [2]	20 ppm vapour
WEL STEL (OEL STEL)	104 mg/m <sup>3</sup> vapour
WEL STEL (OEL STEL) [ppm]	40 ppm vapour
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>Turkey - Occupational Exposure Limits</b>	
Local name	Etilen glikol
OEL TWA	52 mg/m <sup>3</sup>
OEL TWA [ppm]	20 ppm
OEL STEL	104 mg/m <sup>3</sup>
OEL STEL [ppm]	40 ppm
Comments	Deri
Regulatory reference	12 Ağustos 2013 Tarihli ve 28733 Sayılı Resmî Gazete
<b>Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	White spirit Type 1
IOEL TWA [ppm]	20 ppm
IOEL STEL	290 mg/m <sup>3</sup>
IOEL STEL [ppm]	50 ppm
Notes	Skin. (Year of adoption 2007)
Regulatory reference	SCOEL Recommendations
<b>Hydrotreated Heavy naphtha - benzene &lt;0.1% (64742-48-9)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	White spirit Type 3
IOEL TWA [ppm]	20 ppm
IOEL STEL	290 mg/m <sup>3</sup>
IOEL STEL [ppm]	50 ppm
Notes	Skin. (Year of adoption 2007)
Regulatory reference	SCOEL Recommendations
<b>propionic acid ... % (79-09-4)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Propionic acid
IOEL TWA [ppm]	10 ppm
IOEL STEL	62 mg/m <sup>3</sup>
IOEL STEL [ppm]	20 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>propionic acid ... % (79-09-4)</b>	
<b>Austria - Occupational Exposure Limits</b>	
Local name	Propionsäure
MAK (OEL TWA)	31 mg/m <sup>3</sup>
MAK (OEL TWA) [ppm]	10 ppm
MAK (OEL STEL)	62 mg/m <sup>3</sup> (4x 15(Miw) min)
MAK (OEL STEL) [ppm]	20 ppm (4x 15(Miw) min)
Regulatory reference	BGBI. II Nr. 382/2020
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Acide propionique # Propionzuur
OEL TWA	31 mg/m <sup>3</sup>
OEL TWA [ppm]	10 ppm
OEL STEL	62 mg/m <sup>3</sup>
OEL STEL [ppm]	20 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020
<b>Czech Republic - Occupational Exposure Limits</b>	
Local name	Kyselina propionová (Kyselina propanová)
PEL (OEL TWA)	30 mg/m <sup>3</sup>
PEL (OEL TWA) [ppm]	10 ppm
NPK-P (OEL C)	60 mg/m <sup>3</sup>
NPK-P (OEL C) [ppm]	20 ppm
Remark (CZ)	I - dráždí sliznice (oči, dýchací cesty), respektive kůži.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 41/2020 Sb.)
<b>Estonia - Occupational Exposure Limits</b>	
Local name	Propaanhape (propioonhape)
OEL TWA	30 mg/m <sup>3</sup>
OEL TWA [ppm]	10 ppm
OEL STEL	62 mg/m <sup>3</sup>
OEL STEL [ppm]	20 ppm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 17.10.2019, 2); Vabariigi Valitsuse 10. märtsi 2019. a määruse nr 84
<b>Finland - Occupational Exposure Limits</b>	
Local name	Propionihappo
HTP (OEL TWA) [1]	31 mg/m <sup>3</sup>
HTP (OEL TWA) [2]	10 ppm
HTP (OEL STEL)	61 mg/m <sup>3</sup>
HTP (OEL STEL) [ppm]	20 ppm
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
<b>Greece - Occupational Exposure Limits</b>	
Local name	Προπιονικό οξύ

# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

propionic acid ... % (79-09-4)	
OEL TWA	30 mg/m <sup>3</sup>
OEL TWA [ppm]	10 ppm
OEL STEL	60 mg/m <sup>3</sup>
OEL STEL [ppm]	20 ppm
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Italy - Occupational Exposure Limits	
Local name	Acido propionico
OEL TWA	31 mg/m <sup>3</sup>
OEL TWA [ppm]	10 ppm
OEL STEL	62 mg/m <sup>3</sup>
OEL STEL [ppm]	20 ppm
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
Netherlands - Occupational Exposure Limits	
Local name	Propionzuur
MAC-TGG (OEL TWA)	31 mg/m <sup>3</sup>
MAC-15 (OEL STEL)	62 mg/m <sup>3</sup>
Regulatory reference	Arbeidsomstandighedenregeling 2020
Romania - Occupational Exposure Limits	
Local name	Acid propionic
OEL TWA	31 mg/m <sup>3</sup>
OEL TWA [ppm]	10 ppm
OEL STEL	62 mg/m <sup>3</sup>
OEL STEL [ppm]	20 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 157/2020)
United Kingdom - Occupational Exposure Limits	
Local name	Propionic acid
WEL TWA (OEL TWA) [1]	31 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	10 ppm
WEL STEL (OEL STEL)	46 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	15 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Turkey - Occupational Exposure Limits	
Local name	Propionikasit
OEL TWA	31 mg/m <sup>3</sup>
OEL TWA [ppm]	10 ppm
OEL STEL	62 mg/m <sup>3</sup>
OEL STEL [ppm]	20 ppm
Regulatory reference	12 Ağustos 2013 Tarihli ve 28733 Sayılı Resmî Gazete

# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Chemical resistant gloves (according to European standard NF EN 374 or equivalent). Protective gloves made of PVC. neoprene gloves. Nitrile rubber gloves

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

Wear appropriate mask

Respiratory protection			
Device	Filter type	Condition	Standard
	Type A - High-boiling (>65 °C) organic compounds		

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Colour : orange.  
Odour : characteristic.

# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Odour threshold	: Not available
Melting point	: - 31 °C (Styrene)
Freezing point	: Not available
Boiling point	: 145 °C (Styrene)
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosive limit (LEL)	: 1.1 %(V) (Styrene)
Upper explosive limit (UEL)	: 6.1 %(V) (Styrene)
Flash point	: 31 °C (Styrene)
Auto-ignition temperature	: 490 °C (Styrene)
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: Not available
Relative density	: 1
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Harmful if inhaled.

#### NORESTER 680 THIXO PRE\_ACCELERATED

ATE CLP (dust,mist)	2,928 mg/l/4h
---------------------	---------------

#### Styrene (100-42-5)

LD50 oral rat	≈ 5000 mg/kg
LD50 dermal rat	2000 mg/kg
LC50 Inhalation - Rat	11,8 mg/l

#### MONOETHYLENE GLYCOL (107-21-1)

LD50 oral rat	7712 mg/kg bodyweight Animal: rat
LD50 dermal	> 3500 mg/kg mouse
LC50 Inhalation - Rat	> 2,5 mg/l 6 h

#### Cobalt bis(2-ethylhexanoate) (136-52-7)

LD50 oral rat	3129 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), 95% CL: 1750 - 5000
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

#### Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
---------------	--

#### Hydrotreated Heavy naphtha - benzene <0.1% (64742-48-9)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
---------------	--

#### propionic acid ... % (79-09-4)

LD50 oral rat	3455,1 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 2978,9 - 4007,5
LD50 dermal rat	3235 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 20 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

#### MONOETHYLENE GLYCOL (107-21-1)

NOAEL (chronic, oral, animal/male, 2 years)	1500 mg/kg bodyweight Animal: mouse, Animal sex: male, Remarks on results: other:Effect type: carcinogenicity (migrated information)
---	--

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause respiratory irritation.

#### Styrene (100-42-5)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

### Hydrotreated Heavy naphtha - benzene <0.1% (64742-48-9)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

### Styrene (100-42-5)

STOT-repeated exposure	Causes damage to organs (hearing organs) through prolonged or repeated exposure.
------------------------	--

### MONOETHYLENE GLYCOL (107-21-1)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

### Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1)

STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure. Not classified.
------------------------	---

Aspiration hazard : Not classified

## 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

### Styrene (100-42-5)

LC50 - Fish [1]	4,02 mg/l (96 h) (Pimephales promelas)
EC50 - Crustacea [1]	4,7 mg/l (48 h) (Daphnia magna)
EC50 72h - Algae [1]	4,9 mg/l (Pseudokirchneriella subcapitata)
ErC50 algae	4,9 mg/l (Pseudokirchneriella subcapitata)

### MONOETHYLENE GLYCOL (107-21-1)

LC50 - Fish [1]	72860 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	3536 mg/l Test organisms (species): other:greenn algae
EC50 96h - Algae [2]	6500 – 13000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 1000 mg/l Test organisms (species): Americamysis bahia (previous name: Mysidopsis bahia) Duration: '23 d'
NOEC chronic fish	15380 mg/l Pimephales Promelas
NOEC chronic crustacea	8590 mg/l Ceriodaphnia Dubia

### Hydrotreated Heavy naphtha - benzene <0.1% (64742-48-9)

LC50 - Fish [1]	> 1000 mg/l Oncorhynchus mykiss (Rainbow trout)
EC50 - Crustacea [1]	> 1000 mg/l



# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### Hydrotreated Heavy naphtha - benzene <0.1% (64742-48-9)

EC50 72h - Algae [1]	> 1000 mg/l
----------------------	-------------

### propionic acid ... % (79-09-4)

LC50 - Fish [1]	> 10000 mg/l Test organisms (species): Leuciscus idus
-----------------	---

EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): Daphnia magna
----------------------	--

EC50 72h - Algae [1]	> 500 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
----------------------	---

## 12.2. Persistence and degradability

### MONOETHYLENE GLYCOL (107-21-1)

Biodegradation	90 – 100 %
----------------	------------

## 12.3. Bioaccumulative potential

### Styrene (100-42-5)

Partition coefficient n-octanol/water (Log Pow)	2,96
---	------

## 12.4. Mobility in soil

No additional information available

## 12.5. Results of PBT and vPvB assessment

No additional information available

## 12.6. Endocrine disrupting properties

No additional information available

## 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Additional information : Flammable vapours may accumulate in the container.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

### 14.1. UN number or ID number

UN-No. (ADR) : UN 1866  
UN-No. (IMDG) : UN 1866  
UN-No. (IATA) : UN 1866

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : RESIN SOLUTION  
Proper Shipping Name (IMDG) : RESIN SOLUTION  
Proper Shipping Name (IATA) : Resin solution  
Transport document description (ADR) : UN 1866 RESIN SOLUTION, 3, III, (D/E)  
Transport document description (IMDG) : UN 1866 RESIN SOLUTION, 3, III  
Transport document description (IATA) : UN 1866 Resin solution, 3, III

# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : 3  
Danger labels (ADR) : 3



#### IMDG

Transport hazard class(es) (IMDG) : 3  
Danger labels (IMDG) : 3



#### IATA

Transport hazard class(es) (IATA) : 3  
Danger labels (IATA) : 3



### 14.4. Packing group

Packing group (ADR) : III  
Packing group (IMDG) : III  
Packing group (IATA) : III


### 14.5. Environmental hazards

Dangerous for the environment : No  
Marine pollutant : No  
Other information : No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

Special provisions (ADR) : 640E  
Transport category (ADR) : 3  
Hazard identification number (Kemler No.) : 30  
Orange plates :



Tunnel restriction code (ADR) : D/E  
EAC code : •3YE

#### Transport by sea

EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-E  
Stowage category (IMDG) : A  
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### Air transport

PCA packing instructions (IATA) : 355  
CAO packing instructions (IATA) : 366  
ERG code (IATA) : 3L

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

#### 15.1.2. National regulations

##### Netherlands

SZW-lijst van kankerverwekkende stoffen : Naphtha (petroleum), hydrodesulfurized heavy,Hydrotreated Heavy naphtha - benzene <0.1% are listed

SZW-lijst van mutagene stoffen : Naphtha (petroleum), hydrodesulfurized heavy,Hydrotreated Heavy naphtha - benzene <0.1% are listed

NIET-limitatieve lijst van voor de voortplanting : None of the components are listed

giftige stoffen – Borstvoeding

NIET-limitatieve lijst van voor de voortplanting : None of the components are listed

giftige stoffen – Vruchtbaarheid

NIET-limitatieve lijst van voor de voortplanting : Styrene is listed

giftige stoffen – Ontwikkeling

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Indication of changes

Section	Changed item	Change	Comments
	Supersedes version of	Modified	
	Revision date	Modified	
1.2	Main use category	Added	
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified	
2.2	Hazard statements (CLP)	Modified	
11.1	ATE CLP (dust,mist)	Modified	

### Full text of H- and EUH-statements

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1

# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements	
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. Not classified	Carcinogenicity Not classified
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. Not classified	Germ cell mutagenicity Not classified
Repr. 1B	Reproductive toxicity, Category 1B
Repr. 2	Reproductive toxicity, Category 2
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT RE Not classified	Specific target organ toxicity (repeated exposure) Not classified
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H360F	May damage fertility.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

# UC1 Uni-Mould™ Coupling Coat

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

---

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]		
Flam. Liq. 3	H226	Calculation method
Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Repr. 2	H361	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 1	H372	Calculation method
Aquatic Chronic 3	H412	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.