



## SAFETY DATA SHEET

PC15 Water Clear Polyurethane Casting Resin Part A

Page: 1

Compilation date: 05/09/2017

Revision date: 05/09/2017

Revision No: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** PC15 Water Clear Polyurethane Part A

**Product code:** PC15

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC1: Adhesives, sealants. PC9a: Coatings and paints, thinners, paint removers. PC9b: Fillers, putties, plasters, modelling clay. PC32: Polymer preparations and compounds. PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of preparations\* and articles (multistage and/or significant contact) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring PROC19: Hand-mixing with intimate contact and only PPE available ERC2: Formulation of preparations\* ERC3: Formulation in materials ERC5: Industrial use resulting in inclusion into or onto a matrix ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** Easy Composites Ltd  
Unit 39, Park Hall Business Village  
Longton, Stoke on Trent  
Staffordshire  
ST3 5XA  
United Kingdom  
**Tel:** +44 (0) 1782 454499  
**Fax:** +44 (0) 1782 596868  
**Email:** sales@easycomposites.co.uk

# SAFETY DATA SHEET

PC15 Water Clear Polyurethane Casting Resin Part A

Page: 2

## 1.4. Emergency telephone number

**Emergency tel:** +44 (0) 1782 454499  
(office hours only)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Sens. 1A: H317

**Most important adverse effects:** Harmful if swallowed. May cause an allergic skin reaction. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

### 2.2. Label elements

**Label elements:**

**Hazard statements:** H302: Harmful if swallowed.  
H317: May cause an allergic skin reaction.  
H400: Very toxic to aquatic life.  
H410: Very toxic to aquatic life with long lasting effects.

**Hazard pictograms:** GHS07: Exclamation mark  
GHS09: Environmental



**Signal words:** Warning

**Precautionary statements:** P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P301+312: IF SWALLOWED: Call a if you feel unwell.  
P302+352: IF ON SKIN: Wash with plenty of water/.  
P321: Specific treatment (see instructions on this label).  
P330: Rinse mouth.

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

**Hazardous ingredients:**

PENTAERYTHRITOL TETRAKIS(3-MERCAPTOPROPIONATE) - REACH registered number(s): 01-211948698123

EINECS	CAS	PBT / WEL	CLP Classification	Percent
--------	-----	-----------	--------------------	---------

[cont...]

# SAFETY DATA SHEET

PC15 Water Clear Polyurethane Casting Resin Part A

Page: 3

231-472-8	7575-23-7	-	Acute Tox. 4: H302; Skin Sens. 1A: H317; Aquatic Acute 1: H400; Aquatic Chronic 1: H410	>50%
-----------	-----------	---	---	------

3-MERCAPTOPROPIONIC ACID - REACH registered number(s): 01-211948944330

230-537-0	107-96-0	-	Met. Corr. 1: H290; Acute Tox. 3: H301; Acute Tox. 4: H332; Skin Corr. 1B: H314; Eye Dam. 1: H318	0.05-1%
-----------	----------	---	---	---------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** No symptoms.

**Delayed / immediate effects:** No symptoms.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Show this safety data sheet to the doctor in attendance.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol or polymer foam. Carbon dioxide. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes of sulphur oxides. In combustion emits toxic fumes of carbon monoxide.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear protective clothing to prevent contact with skin and eyes. Wear self-contained breathing apparatus.

## Section 6: Accidental release measures

[cont...]

# SAFETY DATA SHEET

PC15 Water Clear Polyurethane Casting Resin Part A

Page: 4

## 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

## 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

## 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

## 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS. Refer to section 13 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Ensure there is exhaust ventilation of the area. Avoid direct contact with the substance. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Keep container tightly closed.  
**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Workplace exposure limits:** No data available.

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is exhaust ventilation of the area.  
**Respiratory protection:** Gas/vapour filter, type A: organic vapours (EN141).  
**Hand protection:** Protective gloves.  
**Eye protection:** Safety glasses. Ensure eye bath is to hand.  
**Skin protection:** Protective clothing.  
**Environmental:** Prevent from entering in public sewers or the immediate environment.

## Section 9: Physical and chemical properties

[cont...]

# SAFETY DATA SHEET

PC15 Water Clear Polyurethane Casting Resin Part A

Page: 5

## 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Colourless

**Odour:** Characteristic odour

**Evaporation rate:** No data available.

**Oxidising:** No data available.

**Solubility in water:** Slightly soluble

**Viscosity:** 350 mPa.s (25°C)

**Boiling point/range°C:** No data available.

**Flammability limits %: lower:** No data available.

**Flash point°C:** 214

**Autoflammability°C:** No data available.

**Relative density:** 1.25 - 1.28

**VOC g/l:** No data available.

**Melting point/range°C:** -40.1

**upper:** No data available.

**Part.coeff. n-octanol/water:** log Pow: 3.03

**Vapour pressure:** 0.0000042hPa at 25C

**pH:** No data available.

## 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

### 10.5. Incompatible materials

**Materials to avoid:** Oxidising agents.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

[cont...]

# SAFETY DATA SHEET

PC15 Water Clear Polyurethane Casting Resin Part A

Page: 6

## Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	ING	Hazardous: calculated
Respiratory/skin sensitisation	-	Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** No symptoms.

**Delayed / immediate effects:** No symptoms.

## Section 12: Ecological information

### 12.1. Toxicity

#### Hazardous ingredients:

#### PENTAERYTHRITOL TETRAKIS(3-MERCAPTOPROPIONATE)

Daphnia magna	48H EC50	0.71	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	0.42	mg/l

### 12.2. Persistence and degradability

**Persistence and degradability:** Not readily biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data available.

### 12.4. Mobility in soil

**Mobility:** No data available.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Very toxic to aquatic organisms.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Waste code number:** 16 05 08

**Disposal of packaging:** Arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

[cont...]

# SAFETY DATA SHEET

PC15 Water Clear Polyurethane Casting Resin Part A

Page: 7

## Section 14: Transport information

### 14.1. UN number

UN number: UN3082

### 14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Pentaerythritol tetra(3-mercaptopropionate))

### 14.3. Transport hazard class(es)

Transport class: 9

### 14.4. Packing group

Packing group: III

### 14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

### 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: -

Transport category: 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H290: May be corrosive to metals.

H301: Toxic if swallowed.

H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H332: Harmful if inhaled.

[cont...]

## SAFETY DATA SHEET

PC15 Water Clear Polyurethane Casting Resin Part A

Page: 8

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.



**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** PC15 Water Clear Polyurethane Part B

**Product code:**

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** PC1: Adhesives, sealants. PC9b: Fillers, putties, plasters, modelling clay. PC9a: Coatings and paints, thinners, paint removers. PC32: Polymer preparations and compounds. PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of preparations\* and articles (multistage and/or significant contact) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring PROC19: Hand-mixing with intimate contact and only PPE available ERC2: Formulation of preparations\* ERC3: Formulation in materials ERC5: Industrial use resulting in inclusion into or onto a matrix ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

**1.3. Details of the supplier of the safety data sheet**

**Company name:** Easy Composites Ltd  
Unit 39, Park Hall Business Village  
Longton, Stoke on Trent  
Staffordshire  
ST3 5XA  
United Kingdom  
**Tel:** +44 (0) 1782 454499  
**Fax:** +44 (0) 1782 596868  
**Email:** sales@easycomposites.co.uk

# SAFETY DATA SHEET

PC15 Water Clear Polyurethane Casting Resin Part B

Page: 2

## 1.4. Emergency telephone number

**Emergency tel:** +44 (0) 1782 454499  
(office hours only)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** STOT SE 3: H335; Acute Tox. 3: H331; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317

**Most important adverse effects:** Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation.

### 2.2. Label elements

#### Label elements:

**Hazard statements:** H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H331: Toxic if inhaled.  
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335: May cause respiratory irritation.

**Hazard pictograms:** GHS06: Skull and crossbones  
GHS08: Health hazard



**Signal words:** Danger

**Precautionary statements:** P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P284: Wear respiratory protection.  
P302+P352: IF ON SKIN: Wash with plenty of water.  
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P362+P364: Take off contaminated clothing and wash it before reuse.

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

[cont...]

# SAFETY DATA SHEET

PC15 Water Clear Polyurethane Casting Resin Part B

Page: 3

## 3.2. Mixtures

### Hazardous ingredients:

4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE) - REACH registered number(s): 01-2119457437-31

EINECS	CAS	PBT / WEL	CLP Classification	Percent
225-863-2	5124-30-1	-	Acute Tox. 3: H331; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	25-50%

HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER - REACH registered number(s): 01-2119485796-17

EINECS	CAS	PBT / WEL	CLP Classification	Percent
500-060-2	28182-81-2	-	STOT SE 3: H335; Acute Tox. 4: H332; Skin Sens. 1: H317	25-50%

HEXAMETHYLENE-DI-ISOCYANATE - REACH registered number(s): 01-211947571-37

EINECS	CAS	PBT / WEL	CLP Classification	Percent
212-485-8	822-06-0	-	Acute Tox. 3: H331; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	0.05-1%

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

[cont...]

# SAFETY DATA SHEET

PC15 Water Clear Polyurethane Casting Resin Part B

Page: 4

## 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

## 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

[cont...]

# SAFETY DATA SHEET

PC15 Water Clear Polyurethane Casting Resin Part B

Page: 5

## 4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE)

### Workplace exposure limits:

### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.02 mg/m <sup>3</sup>	0.07 mg/m <sup>3</sup>	-	-

## HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER

UK	0.02 mg/m <sup>3</sup> (as NCO)	0.07 mg/ms (as NCO)	-	-
----	---------------------------------	---------------------	---	---

## HEXAMETHYLENE-DI-ISOCYANATE

UK	0.02 mg/m <sup>3</sup>	0.07 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

### DNEL/PNEC Values

### Hazardous ingredients:

## 4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE)

Type	Exposure	Value	Population	Effect
DNEL	Dermal	0.6 mg/m <sup>3</sup>	Workers	Local
PNEC	Fresh water	> 0.005 mg/l	-	-
PNEC	Marine water	> 0.0005 mg/l	-	-
PNEC	Soil (agricultural)	> 4.3 mg/kg	-	-
DNEL	Inhalation	0.3 mg/m <sup>3</sup>	Workers	Local
PNEC	Microorganisms in sewage treatment	1.91 mg/l	-	-
PNEC	Fresh water sediments	> 21.75 mg/kg dry we	-	-
PNEC	Marine sediments	> 2.175 mg/kg dry we	-	-

## HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	0.5 mg/m <sup>3</sup>	Workers	Systemic
PNEC	Fresh water	0.127 mg/l	-	-
PNEC	Marine water	0.0127 mg/l	-	-
PNEC	Fresh water sediments	266700 mg/kg	-	-
PNEC	Marine sediments	26670 mg/kg	-	-
PNEC	Soil (agricultural)	53182 mg/kg	-	-
PNEC	Microorganisms in sewage treatment	38.3 mg/l	-	-
DNEL	Inhalation	0.5 mg/m <sup>3</sup>	Workers	Local

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

[cont...]

# SAFETY DATA SHEET

PC15 Water Clear Polyurethane Casting Resin Part B

Page: 6

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Environmental:** Ensure all engineering measures mentioned in section 7 of SDS are in place.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Colourless

**Odour:** Barely perceptible odour

**Evaporation rate:** No data available.

**Oxidising:** No data available.

**Solubility in water:** Reacts with water.

**Viscosity:** 130 mPas (25°C)

**Boiling point/range°C:** No data available.

**Flammability limits %: lower:** No data available.

**Flash point°C:** No data available.

**Autoflammability°C:** No data available.

**Relative density:** 1.08 - 1.13

**VOC g/l:** No data available.

**Melting point/range°C:** No data available.

**upper:** No data available.

**Part.coeff. n-octanol/water:** No data available.

**Vapour pressure:** No data available.

**pH:** No data available.

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

[cont...]

# SAFETY DATA SHEET

PC15 Water Clear Polyurethane Casting Resin Part B

Page: 7

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Hazardous ingredients:

#### 4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE)

DERMAL	RAT	LD50	> 7000	mg/kg
DUST/MIST	RAT	4H LC50	0.33	mg/l
ORL	RAT	LD50	18200	mg/kg

#### HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER

DERMAL	RAT	LD50	>2001	mg/kg
DERMAL	RBT	LD50	>2001	mg/kg
ORAL	RAT	LD50	>2500	mg/kg

#### HEXAMETHYLENE-DI-ISOCYANATE

IVN	MUS	LD50	5600	µg/kg
ORL	MUS	LD50	350	mg/kg
ORL	RAT	LD50	710	µl/kg

#### Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 3)	INH	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	INH DRM	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

[cont...]

# SAFETY DATA SHEET

PC15 Water Clear Polyurethane Casting Resin Part B

Page: 8

## Hazardous ingredients:

### 4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE)

Daphnia magna	EC0 (48h)	>= 8.3	mg/l
Scenedesmus Subspicatus	EC10 (72h)	1.2	mg/l
Scenedesmus Subspicatus	ErC50 (72h)	> 5	mg/l
ZEBRAFISH (Brachydanio rerio)	LC0 (96h)	>= 8.1	mg/l

### HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER

Daphnia magna	48H EC50	>100	mg/l
Scenedesmus Subspicatus	72H ErC50	>1000	mg/l
ZEBRAFISH (Brachydanio rerio)	96H LC50	>100	mg/l

## 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

## 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

## 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

## 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Waste code number:** 08 05 01

**Disposal of packaging:** Arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN2206

### 14.2. UN proper shipping name

**Shipping name:** ISOCYANATES, TOXIC, N.O.S.

[cont...]



# SAFETY DATA SHEET

PC15 Water Clear Polyurethane Casting Resin Part B

Page: 9

(Aliphatic Isocyanates)

## 14.3. Transport hazard class(es)

Transport class: 6.1

## 14.4. Packing group

Packing group: III

## 14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

## 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 2

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.