



SAFETY DATA SHEET

XENCAST® PX30 SOFT FLEXIBLE POLYURETHANE RUBBER

PART A

Page: 1

Compilation date: 05/10/2015

Revision date: 07/07/2021

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: XENCAST® PX30 Soft Flexible Polyurethane Rubber Part A

Product code: PX30-A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants. PC9a: Coatings and paints, thinners, paint removers. PC9b: Fillers, putties, plasters, modelling clay. PC32: Polymer preparations and compounds. PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring PROC19: Hand-mixing with intimate contact and only PPE available ERC2: Formulation of preparations* ERC3: Formulation in materials ERC5: Industrial use resulting in inclusion into or onto a matrix ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

1.3. Details of the supplier of the safety data sheet

Company name: Easy Composites Ltd
Unit 39 Park Hall Business Village
Stoke on Trent
Staffordshire
ST3 5XA
United Kingdom

Tel: +44 (0) 1782 454499

Email: sales@easycomposites.co.uk

SAFETY DATA SHEET

XENCAST® PX30 SOFT FLEXIBLE POLYURETHANE RUBBER - PART A

Page: 2

1.4. Emergency telephone number

Emergency tel: +44 (0) 1782 454499
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Acute Tox. 4: H302; Aquatic Chronic 2: H411; Skin Sens. 1: H317

Most important adverse effects: Harmful if swallowed. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H302: Harmful if swallowed.
H317: May cause an allergic skin reaction.
H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS07: Exclamation mark
GHS09: Environmental



Signal words: Warning

Precautionary statements: P280: Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312: IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
P302+P352: IF ON SKIN: Wash with plenty of water.
P321: Specific treatment (see instructions on this label)
P330: Rinse mouth.
P362+P364: Take off contaminated clothing and wash it before reuse.

Haz. ingredients (label): 1,3-BENZENEDIAMINE, 2(OR 4)-METHYL-4,6(OR 2,6)-BIS(METHYLTHIO)-

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

1,3-BENZENEDIAMINE, 2(OR 4)-METHYL-4,6(OR 2,6)-BIS(METHYLTHIO)- - REACH registered number(s): 01-0000015292-76

EINECS	CAS	PBT / WEL	CLP Classification	Percent
--------	-----	-----------	--------------------	---------

[cont...]

SAFETY DATA SHEET

XENCAST® PX30 SOFT FLEXIBLE POLYURETHANE RUBBER - PART A

Page: 3

403-240-8	106264-79-3	-	Acute Tox. 4: H302; Skin Sens. 1: H317; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	1-25%
-----------	-------------	---	--	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

[cont...]

SAFETY DATA SHEET

XENCAST® PX30 SOFT FLEXIBLE POLYURETHANE RUBBER - PART A

Page: 4

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of mists in the air. Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

Hazardous ingredients:

1,3-BENZEDIAMINE, 2(OR 4)-METHYL-4,6(OR 2,6)-BIS(METHYLTHIO)-

Type	Exposure	Value	Population	Effect
DNEL	Dermal (Chronic)	> 0.39 mg/kg bw/d	Workers	Systemic
DNEL	Inhalation (Acute)	11.8 mg/m ³	Workers	Systemic
DNEL	Inhalation (Chronic)	3.4 mg/m ³	Workers	Systemic
DNEL	Oral (Chronic)	> 0.24 mg/kg bw/d	Consumers	Systemic
DNEL	Dermal (Chronic)	> 0.24 mg/kg bw/d	Consumers	Systemic
DNEL	Inhalation (Chronic)	> 0.94 mg/m ³	Consumers	Systemic
PNEC	Fresh water	8.7 ug/l	-	-
PNEC	Marine water	0.87 ug/l	-	-
PNEC	Fresh water sediments	0.2 mg/kg ww	-	-
PNEC	Marine sediments	0.02 mg/kg ww	-	-

[cont...]

SAFETY DATA SHEET

XENCAST® PX30 SOFT FLEXIBLE POLYURETHANE RUBBER - PART A

Page: 5

PNEC	Soil (agricultural)	0.16 mg/kg ww	-	-
PNEC	Microorganisms in sewage treatment	3.2 mg/l	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Ensure all engineering measures mentioned in section 7 of SDS are in place.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow-orange

Odour: Characteristic odour

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: No data available.

Viscosity: 950 mPa.s (25°C)

Boiling point/range°C: No data available.

Flammability limits %: lower: No data available.

Flash point°C: No data available.

Autoflammability°C: No data available.

Relative density: 1.01 - 1.06

VOC g/l: No data available.

Melting point/range°C: No data available.

upper: No data available.

Part.coeff. n-octanol/water: No data available.

Vapour pressure: No data available.

pH: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

[cont...]

SAFETY DATA SHEET

XENCAST® PX30 SOFT FLEXIBLE POLYURETHANE RUBBER - PART A

Page: 6

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

1,3-BENZENEDIAMINE, 2(OR 4)-METHYL-4,6(OR 2,6)-BIS(METHYLTHIO)-

DERMAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	1515	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	ING	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

1,3-BENZENEDIAMINE, 2(OR 4)-METHYL-4,6(OR 2,6)-BIS(METHYLTHIO)-

DAPHNIA	48H EC50	0.9	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H EC50	7.6	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	7.3	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

[cont...]

SAFETY DATA SHEET

XENCAST® PX30 SOFT FLEXIBLE POLYURETHANE RUBBER - PART A

Page: 7

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Contains: 6-METHYL-2,4-BIS(METHYLTHIO)PHENYLENE-1,3-DIAMINE)

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

[cont...]

SAFETY DATA SHEET

XENCAST® PX30 SOFT FLEXIBLE POLYURETHANE RUBBER - PART A

Page: 8

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H317: May cause an allergic skin reaction.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.



SAFETY DATA SHEET

XENCAST® PX30 SOFT FLEXIBLE POLYURETHANE RUBBER

Page: 1

PART B

Compilation date: 21/06/2016

Revision date: 07/07/2021

Revision No: 7

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: XENCAST® PX30 Soft Flexible Polyurethane Rubber Part B

Product code: PX30-B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants. PC9a: Coatings and paints, thinners, paint removers. PC9b: Fillers, putties, plasters, modelling clay. PC32: Polymer preparations and compounds. PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring PROC19: Hand-mixing with intimate contact and only PPE available ERC2: Formulation of preparations* ERC3: Formulation in materials ERC5: Industrial use resulting in inclusion into or onto a matrix ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

1.3. Details of the supplier of the safety data sheet

Company name: Easy Composites Ltd
Unit 39 Park Hall Business Village
Stoke on Trent
Staffordshire
ST3 5XA
United Kingdom
Tel: +44 (0) 1782 454499
sales@easycomposites.co.uk

SAFETY DATA SHEET

XENCAST® PX30 SOFT FLEXIBLE POLYURETHANE RUBBER - PART B

Page: 2

1.4. Emergency telephone number

Emergency tel: +44 (0) 1782 454499
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; Resp. Sens. 1: H334; STOT RE 2: H373; Aquatic Chronic 1: H410; Asp. Tox. 1: H304; Carc. 2: H351; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335

Most important adverse effects: May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335: May cause respiratory irritation.
H351: Suspected of causing cancer.
H373: May cause damage to organs through prolonged or repeated exposure.
H410: Very toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS07: Exclamation mark
GHS08: Health hazard
GHS09: Environmental



Signal words: Danger

Precautionary statements: P260: Do not breathe dust/fumes/gas/mist/vapours/spray.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P284: Wear respiratory protection.
P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P302+P352: IF ON SKIN: Wash with plenty of water.
P362+P364: Take off contaminated clothing and wash it before reuse.

Haz. ingredients (label): DIISOPROPYLNAPHTHALENE ISOMERS; PREPOLYMER BASED ON AROMATIC POLYISOCYANATE; DIPHENYLMETHANE-2,4'-DI-ISOCYANATE; DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

[cont...]

SAFETY DATA SHEET

XENCAST® PX30 SOFT FLEXIBLE POLYURETHANE RUBBER - PART B

Page: 3

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

DIISOPROPYLNAPHTHALENE ISOMERS - REACH registered number(s): 01-2119565150-48

EINECS	CAS	PBT / WEL	CLP Classification	Percent
254-052-6	38640-62-9	-	Asp. Tox. 1: H304; Aquatic Chronic 1: H410	>50%

PREPOLYMER BASED ON AROMATIC POLYISOCYANATE

-	99784-49-3	-	Eye Irrit. 2: H319; STOT SE 3: H335; STOT RE 2: H373; Aquatic Chronic 2: H411; Acute Tox. 4: H332; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	1-25%
---	------------	---	---	-------

DIPHENYLMETHANE-2,4'-DI-ISOCYANATE - REACH registered number(s): 01-2119480143-45

227-534-9	5873-54-1	-	Carc. 2: H351; Acute Tox. 4: H332; STOT RE 2: H373; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	1-25%
-----------	-----------	---	---	-------

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE - REACH registered number(s): 01-2119457014-47

202-966-0	101-68-8	-	Carc. 2: H351; Acute Tox. 4: H332; STOT RE 2: H373; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	1-25%
-----------	----------	---	---	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If conscious, ensure the casualty sits or lies down. If unconscious and breathing is OK, place in the recovery position. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

[cont...]

SAFETY DATA SHEET

XENCAST® PX30 SOFT FLEXIBLE POLYURETHANE RUBBER - PART B

Page: 4

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat. There may be shortness of breath due to congestion of the lungs.

Inhalation: Exposure may cause coughing or wheezing. There may be congestion of the lungs causing severe shortness of breath.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Alert the neighbourhood to the presence of fumes or gas. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

[cont...]

SAFETY DATA SHEET

XENCAST® PX30 SOFT FLEXIBLE POLYURETHANE RUBBER - PART B

Page: 5

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is exhaust ventilation of the area. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DIPHENYLMETHANE-2,4'-DI-ISOCYANATE

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.02 mg/m ³	0.07 mg/m ³	-	-

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

UK	0.02 mg/m ³	0.07 mg/m ³	-	-
----	------------------------	------------------------	---	---

DNEL/PNEC Values

Hazardous ingredients:

DIPHENYLMETHANE-2,4'-DI-ISOCYANATE

Type	Exposure	Value	Population	Effect
DNEL	Dermal	50 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation	0.1 mg/m ³ air	Workers	Systemic
DNEL	Dermal	28.7 mg/cm ²	Workers	Local
DNEL	Inhalation	0.1 mg/m ³ air	Workers	Local
DNEL	Inhalation (repeated dose)	0.05 mg/m ³ air	Workers	Systemic
DNEL	Inhalation (repeated dose)	0.05 mg/m ³ air	Workers	Local
DNEL	Dermal	25 mg/kg bw/day	General Population	Systemic
DNEL	Inhalation	0.05 mg/m ³ air	General Population	Systemic
DNEL	Oral	20 mg/kg bw/day	General Population	Systemic
DNEL	Dermal	17.2 mg/cm ²	General Population	Local

[cont...]

SAFETY DATA SHEET

XENCAST® PX30 SOFT FLEXIBLE POLYURETHANE RUBBER - PART B

Page: 6

DNEL	Inhalation	0.05 mg/m ³ air	General Population	Local
DNEL	Inhalation (repeated dose)	0.025 mg/m ³ air	General Population	Systemic
DNEL	Inhalation (repeated dose)	0.025 mg/m ³ air	General Population	Local
PNEC	Fresh water	1 mg/l	-	-
PNEC	Marine water	0.1 mg/l	-	-
PNEC	Soil (agricultural)	1 mg/kg dry weight	-	-
PNEC	Microorganisms in sewage treatment	1 mg/l	-	-

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

Type	Exposure	Value	Population	Effect
PNEC	Fresh water	1 mg/l	-	-
PNEC	Marine water	0.1 mg/l	-	-
PNEC	Soil (agricultural)	1 mg dry weight	-	-
PNEC	Microorganisms in sewage treatment	1 mg/l	-	-
DNEL	Inhalation	0.1 mg/m ³	Workers	Systemic
DNEL	Inhalation (repeated dose)	0.05 mg/m ³	Workers	Systemic
DNEL	Inhalation	0.1 mg/m ³	Workers	Local
DNEL	Inhalation (repeated dose)	0.05 mg/m ³	Workers	Local
DNEL	Dermal	50 mg/kg	Workers	Systemic
DNEL	Dermal	28.7 mg/cm ²	Workers	Local
DNEL	Inhalation	0.05 mg/m ³	Consumers	Systemic
DNEL	Inhalation (repeated dose)	0.025 mg/m ³	Consumers	Systemic
DNEL	Inhalation	0.05 mg/m ³	Consumers	Local
DNEL	Inhalation (repeated dose)	0.025 mg/m ³	Consumers	Local
DNEL	Dermal	25 mg/kg	Consumers	Systemic
DNEL	Dermal	17.2 mg/cm ²	Consumers	Local
DNEL	Oral	20 mg/kg	Workers	Systemic

8.2. Exposure controls

Engineering measures: Ensure there is exhaust ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be used in handling.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Ensure all engineering measures mentioned in section 7 of SDS are in place.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

[cont...]

SAFETY DATA SHEET

XENCAST® PX30 SOFT FLEXIBLE POLYURETHANE RUBBER - PART B

Page: 7

Colour: Pale yellow

Odour: Perceptible odour

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Reacts with water.

Viscosity: 60 mPa.s (25°C)

Boiling point/range°C: No data available.

Flammability limits %: lower: No data available.

Flash point°C: No data available.

Autoflammability°C: No data available.

Relative density: 0.98 - 1.03

VOC g/l: No data available.

Melting point/range°C: No data available.

upper: No data available.

Part.coeff. n-octanol/water: No data available.

Vapour pressure: No data available.

pH: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

[cont...]

SAFETY DATA SHEET

XENCAST® PX30 SOFT FLEXIBLE POLYURETHANE RUBBER - PART B

Page: 8

DIISOPROPYLNAPHTHALENE ISOMERS

-	RAT	NOAEL (6 mon)	170	mg/kg/d
DERMAL	RAT	LD50	> 4000	mg/kg
DUST/MIST	RAT	1H LC50	> 5.6	mg/l
ORAL	RAT	LD50	> 4000	mg/kg

PREPOLYMER BASED ON AROMATIC POLYISOCYANATE

DERMAL	RBT	LD50	>9400	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

DIPHENYLMETHANE-2,4'-DI-ISOCYANATE

DERMAL	RBT	LD50	> 9400	mg/kg
ORAL	RAT	LD50	> 2000	mg/kg

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

DERMAL	RBT	LD50	> 9400	mg/kg
DUST/MIST	RAT	1H LC50	> 2.240	mg/l
ORL	RAT	LD50	> 2000	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	INH DRM	Hazardous: calculated
Carcinogenicity	--	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat. There may be shortness of breath due to congestion of the lungs.

Inhalation: Exposure may cause coughing or wheezing. There may be congestion of the lungs causing severe shortness of breath.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

Section 12: Ecological information

[cont...]

SAFETY DATA SHEET

XENCAST® PX30 SOFT FLEXIBLE POLYURETHANE RUBBER - PART B

Page: 9

12.1. Toxicity

Hazardous ingredients:

DIISOPROPYLNAPHTHALENE ISOMERS

ALGAE	72H EC0	0.15	mg/l
DAPHNIA	21D NOEC	0.013	mg/l
DAPHNIA	48H EC0	0.16	mg/l
DAPHNIA	48H LL50	1.7	mg/l
FISH	96H LC0	0.5	mg/l

PREPOLYMER BASED ON AROMATIC POLYISOCYANATE

BACTERIA (Activated sludge)	3H EC50	>100	mg/l
-----------------------------	---------	------	------

DIPHENYLMETHANE-2,4'-DI-ISOCYANATE

BACTERIA (Activated Sludge)	3H EC50	> 100	mg/l
-----------------------------	---------	-------	------

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

Activated sludge	3H EC50	> 100	mg/l
Daphnia magna	24H EC50	> 1000	mg/l
Scenedesmus Subspicatus	72H EC0	1640	mg/l
ZEBRAFISH (Brachydanio rerio)	96H LC0	> 1000	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 08 05 01

Disposal of packaging: Arrange for collection by specialised disposal company.

[cont...]

SAFETY DATA SHEET

XENCAST® PX30 SOFT FLEXIBLE POLYURETHANE RUBBER - PART B

Page: 10

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Contains: DIISOPROPYLNAPHTHALENE ISOMERS)

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

[cont...]

SAFETY DATA SHEET

XENCAST® PX30 SOFT FLEXIBLE POLYURETHANE RUBBER - PART B

Page: 11

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H351: Suspected of causing cancer.

H373: May cause damage to organs through prolonged or repeated exposure.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.