

## **Woven Glass Cloth**

## **DESCRIPTION**

Genral Purpose Woven Glass Fibre Reinforcement, 280g/m<sup>2</sup>.

This 1 metre wide woven 'E' glass does not include any chemical binders and therefore is suitable for use with any resin system including epoxy, polyester and vinylester.

USES

This general Purpose 280gsm woven glass fabric is a very high performance E glass perfect for more advanced composites use. At 280gsm the fabric is the weight of choice for projects such as radio controlled planes, UAVs, robotics and other precision applications.

## **PROPERTIES**

Glass Type		:EGLASS twill	Filament Diameter : 13μm	
Density		weave :8×7ends/cm	Sizing	Epoxy compatible
Yarns	Warp	: EC13-66X3TEX		
use	Weft	EC13-66X3TEX	Color	White

Moisture content	≤0.20%	
Density	Warp	8±0,7
(ends/cm)	Weft	7 <u>±</u> 0,6
Tensile strength (N/25*200mm)	Warp	≥2200
(14/25/20011111)	Weft	≥2000
Mass(g/m2)	300±24	
Width(cm)	100±1.0	
Length(m)	100±2.0	
Paper tube inner	76 mm	
Recommended S	25°C	
Humidity	61%	

## Disclaimer

This data is not to be used for specifications. Values listed are for typical properties and should not be considered minimum or maximum.

Our technical advice, whether verbal or in writing, is given in good faith but Easy Composites Ltd gives no warranty; express or implied, and all products are sold upon condition that purchasers will make their own tests to determine the quality and suitability of the product for their particular application and circumstances.

Easy Composites Ltd shall be in no way responsible for the proper use and service of the product, nor for the safeguarding of personnel or property, all of which is the duty of the user. Any information or suggestions are without warranty of any kind and purchasers are solely responsible for any loss arising from the use of such information or suggestions. No information or suggestions given by us shall be deemed to be a recommendation to use any product in conflict with any existing patent rights. Before using any of our products, users should familiarise themselves with the relevant technical and safety datasheets provided by Easy Composites Ltd.