

West & Senior Limited

Milltown Street • Radcliffe • Manchester • M26 1WE • United Kingdom Tel +44 (0) 161 724 7131 • Fax +44 (0) 161 724 9519 http://www.westsenior.co.uk • info@westsenior.co.uk

SAFETY DATA SHEET EP FASCOL TANGERINE PIGMENT

SECTION 1: Identification of t	the substance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	EP FASCOL TANGERINE PIGMENT
Product number	WS40528A
1.2. Relevant identified uses	of the substance or mixture and uses advised against
Identified uses	COLOURING OF EPOXIDE COMPOUNDS & SYSTEMS
1.3. Details of the supplier of	the safety data sheet
Supplier	WEST AND SENIOR LIMITED. MILLTOWN STREET RADCLIFFE MANCHESTER. M26 1WE. TEL + 44 01617247131 FAX + 44 01617249519 info@westsenior.co.uk
1.4. Emergency telephone nu	imber
Emergency telephone	24 HOUR EMERGENCY TELEPHONE NUMBER : + 44 (0) 7930 595916
SECTION 2: Hazards identified	cation
2.1. Classification of the subs	tance or mixture
Classification (EC 1272/2008)	-
Physical hazards	Not Classified
Health hazards	Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317
Environmental hazards	Aquatic Chronic 2 - H411
Human health	See Section 11 for additional information on health hazards.
Environmental	The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.
2.2. Label elements	
Hazard pictograms	
Signal word	Warning
Hazard statements	H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects.

Precautionary statements	 P261 Avoid breathing vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage. P501 Dispose of contents/ container in accordance with national regulations.
Supplemental label information	EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Contains	bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700, oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

bis-[4-(2,3-epoxipropoxi)phenyl]p	ropane	30-60%
CAS number: 1675-54-3	EC number: 216-823-5	REACH registration number: 01- 2119456619-26
Classification		
Skin Irrit. 2 - H315		
Eye Irrit. 2 - H319		
Skin Sens. 1 - H317		
Aquatic Chronic 2 - H411		
Aqualic Chronic 2 - 11411		
Formaldehyde, polymer with (chle phenol, mw <=700	oromethyl)oxirane and	10-30%
Formaldehyde, polymer with (chl	oromethyl)oxirane and EC number: 500-006-8	10-30% REACH registration number: 01-
Formaldehyde, polymer with (chlo phenol, mw <=700		
Formaldehyde, polymer with (chlo phenol, mw <=700		REACH registration number: 01-
Formaldehyde, polymer with (chlo phenol, mw <=700 CAS number: 9003-36-5		REACH registration number: 01-
Formaldehyde, polymer with (chlo phenol, mw <=700 CAS number: 9003-36-5 Classification		REACH registration number: 01-

TITANIUM DIOXIDE		5-10%
CAS number: 13463-67-7	EC number: 236-675-5	REACH registration number: 01- 2119489379-17-0000
Classification Not Classified		
oxirane, mono[(C12-14-alky	loxy)methyl] derivs.	5-10%
CAS number: 68609-97-2	REACH registration number: 01- 2119485289-22-0000	
Classification Skin Irrit. 2 - H315 Skin Sens. 1 - H317		
Amines, N-coco alkyltrimeth	ylenedi-	<1%
CAS number: 61791-63-7 M factor (Acute) = 10	EC number: 263-195-3	
Classification Acute Tox. 4 - H302 Skin Corr. 1A - H314 Aquatic Acute 1 - H400		
CARBON BLACK		<1%
CAS number: 1333-86-4	EC number: 215-609-9	REACH registration number: 01- 2119384822-32-0000
Classification Not Classified		
The full text for all hazard sta	itements is displayed in Section 16.	
Composition comments	This mixture contains ≥ 1% Titanium Dioxide Titanium Dioxide does not apply to this mixtur	(CAS 13463-67-7) The Annex VI classification of e according to its Note 10.
SECTION 4: First aid measu	res	
4.1. Description of first aid m	easures	
Inhalation	Move affected person to fresh air at once. If b When breathing is difficult, properly trained pe administering oxygen. Keep affected person v immediately.	ersonnel may assist affected person by
Ingestion	Never give anything by mouth to an unconscion mouth thoroughly with water. Give milk instean attention immediately.	
Skin contact	Remove affected person from source of conta immediately and wash skin with soap and wat continues.	

Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention promptly if symptoms occur after washing.	
4.2. Most important symptoms	and effects, both acute and delayed	
Inhalation	Vapours may irritate throat/respiratory system.	
Ingestion	There may be soreness and redness of the mouth and throat.	
Skin contact	Prolonged contact may cause redness, irritation and dry skin.	
Eye contact	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.	
4.3. Indication of any immedia	te medical attention and special treatment needed	
Notes for the doctor	No specific recommendations. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.	
Specific treatments	Provide eyewash station.	
SECTION 5: Firefighting meas	sures	
5.1. Extinguishing media		
Suitable extinguishing media	Use fire-extinguishing media suitable for the surrounding fire.	
Unsuitable extinguishing media	Not known.	
5.2. Special hazards arising from	om the substance or mixture	
Specific hazards	Fire or high temperatures create: Toxic gases/vapours/fumes of: Carbon dioxide (CO2). Carbon monoxide (CO). Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.	
Hazardous combustion products	Carbon dioxide (CO2). Carbon monoxide (CO). Halogenated hydrocarbons.	
5.3. Advice for firefighters		
Protective actions during firefighting	Isolate area. Very toxic to aquatic life. Control run-off water by containing and keeping it out of sewers and watercourses.	
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Use air-supplied respirator, gloves and protective goggles.	
SECTION 6: Accidental release	e measures	
6.1. Personal precautions, pro	tective equipment and emergency procedures	
Personal precautions	For personal protection, see Section 8. Keep unnecessary and unprotected personnel from entering the area. Avoid inhalation of vapours. Isolate area.	
6.2. Environmental precautions		
Environmental precautions	Avoid discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.	
6.3. Methods and material for	containment and cleaning up	
Methods for cleaning up	Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses. For waste disposal, see Section 13.	

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. See Section 11 for additional information on health hazards. Collect and dispose of spillage as indicated in Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling Usage precautions Do not eat, drink or smoke when using this product. Persons susceptible to allergic reactions should not handle this product. Avoid contact with skin and eyes. Avoid inhalation of vapours and spray/mists. Store in tightly-closed, original container. Wear suitable protective clothing as protection against splashing or contamination. 7.2. Conditions for safe storage, including any incompatibilities Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Storage class Chemical storage. 7.3. Specific end use(s) Specific end use(s) The identified uses for this product are detailed in Section 1.2. SECTION 8: Exposure controls/Personal protection 8.1. Control parameters

Occupational exposure limits

TITANIUM DIOXIDE

EH40 WEL, Time Weighted Average (TWA):, Inhalable dust. 10 mg/m3, 8 h EH40 WEL, Time Weighted Average (TWA):, Respirable dust. 4 mg/m3, 8 h

CARBON BLACK

Argentina 3.5, TWA Australia 3.0, TWA, inhalable Belgium 3.6, TWA Brazil 3.5, TWA Canada (Ontario) 3.0 TWA, inhalable China 4.0, TWA 8.0, TWA, STEL (15 min) Colombia 3.0, TWA, inhalable Czech Republic 2.0, TWA Egypt 3.5, TWA Finland 3.5, TWA; 7.0, STEL France - INRS 3.5, TWA/VME inhalable Germany – BeKGS527 0.5, TWA, respirable; 2.0, TWA, inhalable (DNEL values) Hong Kong 3.5, TWA Indonesia 3.5, TWA/NABs Ireland 3.5, TWA; 7.0, STEL Italy 3.5, TWA, inhalable Japan - MHLW 3.0 Japan - SOH 4.0, TWA; 1.0, TWA, respirable Korea 3.5, TWA Malaysia 3.5, TWA Mexico 3.5, TWA Russia 4.0, TWA Spain 3.5, TWA (VLA-ED) Sweden 3.0, TWA United Kingdom 3.5, TWA, inhalable; 7.0, STEL, inhalable EU REACH DNEL 2.0, TWA, inhalable; 0.5, TWA respirable United States 3.5, TWA, OSHA-PEL 3.0, TWA, ACGIH-TLV®, inhalable 3.5, TWA, NIOSH-REL

bis-[4-(2,3-epoxipropoxi)phenyl]propane (CAS: 1675-54-3)

DNEL	Workers - Dermal; Short term systemic effects: 8.3 mg/kg, bw/day Workers - Inhalation; Short term systemic effects: 12.3 mg/m ³ Workers - Dermal; Long term systemic effects: 8.3 mg/kg, bw/day Workers - Inhalation; Long term systemic effects: 12.3 mg/m ³ General population - Dermal; Short term systemic effects: 3.6 mg/kg, bw/day General population - Inhalation; Short term systemic effects: 0.75 mg/m ³ General population - Oral; Short term systemic effects: 0.75 mg/kg, bw/day General population - Dermal; Long term systemic effects: 0.75 mg/kg, bw/day General population - Inhalation; Long term systemic effects: 0.75 mg/m ³ General population - Inhalation; Long term systemic effects: 0.75 mg/m ³
PNEC	Fresh water; 3 µg/l marine water; 0.3 µg/l STP; 10 mg/l Sediment (Freshwater); 0.5 mg/kg Sediment (Marinewater); 0.5 mg/kg Sediment; 0.05 mg/kg Intermittent release; 0.013 mg/l
Formaldehyde, p	oolymer with (chloromethyl)oxirane and phenol, mw <=700 (CAS: 9003-36-5)

DNEL	Industry - Dermal; Short term local effects: 8.3 ppm Industry - Dermal; Long term systemic effects: 104.15 mg/kg/day Industry - Inhalation; Long term systemic effects: 29.39 mg/m ³ Consumer - Dermal; Long term systemic effects: 62.5 mg/kg/day Consumer - Inhalation; Long term systemic effects: 8.7 mg/m ³ Consumer - Oral; Long term systemic effects: 6.25 mg/kg/day
PNEC	 Fresh water; 0.003 mg/l marine water; 0.0003 mg/l Sediment (Freshwater); 0.294 mg/kg Sediment (Marinewater); 0.0294 mg/kg Soil; 0.237 mg/kg Intermittent release; 0.0254
	C.I. PIGMENT YELLOW 83 (CAS: 5567-15-7)
DNEL	Workers - Dermal; Long term systemic effects: 45 mg/kg/day Workers - Inhalation; Long term local effects: 3 mg/m ³ General population - Dermal; Long term systemic effects: 28 mg/kg/day General population - Oral; Long term systemic effects: 28 mg/kg/day
	TITANIUM DIOXIDE (CAS: 13463-67-7)
DNEL	Workers - Inhalation; Long term local effects: 10 mg/m³ Professional - Inhalation; Long term local effects: 10 mg/m³ Consumer - Oral; Long term systemic effects: 700 mg/kg/day
PNEC	marine water; 0.0184 mg/l Fresh water; 0.184 mg/l Intermittent release; 0.193 mg/l STP; 100 mg/l Sediment, marine water; 100 mg/kg Sediment, Fresh water; 1000 mg/kg Soil; 100 mg/kg
ox	tirane, mono[(C12-14-alkyloxy)methyl] derivs. (CAS: 68609-97-2)
DNEL	Workers - Inhalation; Long term systemic effects: 3.6 mg/m ³ Workers - Dermal; Long term systemic effects: 1 mg/kg/day General population - Inhalation; Long term systemic effects: 0.87 mg/m ³ General population - Dermal; Long term systemic effects: 0.5 mg/kg/day General population - Oral; Long term systemic effects: 0.5 mg/kg/day
PNEC	Fresh water; 0.106 mg/l Fresh water, Intermittent release; 0.072 mg/l marine water; 0.011 mg/l STP; 10 mg/l Sediment (Freshwater), dw; 307.16 mg/kg Sediment (Marinewater), dw; 30.72 mg/kg Soil, dw; 1.234 mg/kg
	CARBON BLACK (CAS: 1333-86-4)
DNEL	Workers - Inhalation; Long term : 0.5 mg/m³, respirable fraction Workers - Inhalation; Long term : 2 mg/m³, inhalable fraction

Trimethylolpropane (CAS: 77-99-6)

DNEL	Workers - Inhalation; Long term systemic effects: 3.3 mg/m ³ Workers - Dermal; Long term systemic effects: 0.94 mg/kg Consumer - Inhalation; Long term systemic effects: 0.58 mg/m ³ Consumer - Dermal; Long term systemic effects: 0.34 mg/kg Consumer - Oral; Long term systemic effects: 0.34 mg/kg
8.2. Exposure controls	
Protective equipment	
Appropriate engineering controls	Provide adequate general and local exhaust ventilation.
Eye/face protection	Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Chemical splash goggles.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.
Other skin and body protection	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
Hygiene measures	Provide eyewash station. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Check that the respirator fits tightly and the filter is changed regularly.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid. or Coloured paste.
Colour	Various colours.
Odour	Slight.
Odour threshold	Not available.
рН	Not available.
Melting point	Not determined.
Initial boiling point and range	Not determined.
Flash point	150°C
Evaporation rate	Not determined.
Evaporation factor	Not available.
Flammability (solid, gas)	Not available.

Upper/lower flammability or explosive limits	Not determined.
Other flammability	Not available.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	Not available.
Bulk density	Not available.
Solubility(ies)	Not available.
Partition coefficient	Not available.
Auto-ignition temperature	(ASTM D 1929) 400°C
Decomposition Temperature	Not available.
Viscosity	Not determined.
Explosive properties	Not applicable.
Explosive under the influence of a flame	No
Oxidising properties	Not available.
Comments	Information given is applicable to the product as supplied.
9.2. Other information	
Other information	No information required.
Other information SECTION 10: Stability and rea	
SECTION 10: Stability and rea	
SECTION 10: Stability and rea	ctivity
SECTION 10: Stability and rea 10.1. Reactivity Reactivity	ctivity
SECTION 10: Stability and real 10.1. Reactivity Reactivity 10.2. Chemical stability Stability 10.3. Possibility of hazardous of	Stable at normal ambient temperatures and when used as recommended. No particular stability concerns.
SECTION 10: Stability and rea 10.1. Reactivity Reactivity 10.2. Chemical stability Stability	Stable at normal ambient temperatures and when used as recommended. No particular stability concerns.
SECTION 10: Stability and real 10.1. Reactivity Reactivity 10.2. Chemical stability Stability 10.3. Possibility of hazardous Possibility of hazardous	Stable at normal ambient temperatures and when used as recommended. No particular stability concerns. reactions
SECTION 10: Stability and real 10.1. Reactivity Reactivity 10.2. Chemical stability Stability 10.3. Possibility of hazardous Possibility of hazardous reactions	Stable at normal ambient temperatures and when used as recommended. No particular stability concerns. reactions
SECTION 10: Stability and reading 10.1. Reactivity Reactivity 10.2. Chemical stability Stability 10.3. Possibility of hazardous Possibility of hazardous reactions 10.4. Conditions to avoid Conditions to avoid 10.5. Incompatible materials	Instructivity Stable at normal ambient temperatures and when used as recommended. No particular stability concerns. Image: Teactions Hazardous reactions or instability may occur under certain conditions of storage or use. Avoid releasing into the environment.
SECTION 10: Stability and real 10.1. Reactivity Reactivity 10.2. Chemical stability Stability 10.3. Possibility of hazardous Possibility of hazardous reactions 10.4. Conditions to avoid Conditions to avoid	activity Stable at normal ambient temperatures and when used as recommended. No particular stability concerns. reactions Hazardous reactions or instabillity may occur under certain conditions of storage or use.
SECTION 10: Stability and reading 10.1. Reactivity Reactivity 10.2. Chemical stability Stability 10.3. Possibility of hazardous Possibility of hazardous reactions 10.4. Conditions to avoid Conditions to avoid 10.5. Incompatible materials Materials to avoid 10.6. Hazardous decomposition	Instituty Stable at normal ambient temperatures and when used as recommended. No particular stability concerns. Instability concerns. Hazardous reactions or instability may occur under certain conditions of storage or use. Avoid releasing into the environment. No data recorded. In products
SECTION 10: Stability and reading 10.1. Reactivity Reactivity 10.2. Chemical stability Stability 10.3. Possibility of hazardous Possibility of hazardous reactions 10.4. Conditions to avoid Conditions to avoid 10.5. Incompatible materials Materials to avoid	Instructivity Stable at normal ambient temperatures and when used as recommended. No particular stability concerns. reactions Hazardous reactions or instability may occur under certain conditions of storage or use. Avoid releasing into the environment. No data recorded.

11.1. Information on toxicological effects

Toxicological information on ingredients.

	bis-[4-(2,3-epoxipropoxi)phenyl]propane
Acute toxicity - oral	
Notes (oral LD₅₀)	LD₅₀ 11400 mg/kg, Oral, Rat
Acute toxicity - dermal	
Notes (dermal LD ₅₀)	LD₅₀ >2000 mg/kg, Dermal, Rabbit
Acute toxicity - inhalation	
Notes (inhalation LC_{50})	Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at ambient temperature.
Skin corrosion/irritation	
Skin corrosion/irritation	Irritating to skin.
Serious eye damage/irritati	on
Serious eye damage/irritation	Causes eye irritation.
Respiratory sensitisation	
Respiratory sensitisation	May cause sensitisation or allergic reactions in sensitive individuals.
Skin sensitisation	
Skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Based on available data the classification criteria are not met.
Carcinogenicity	
IARC carcinogenicity	IARC Group 3 Not classifiable as to its carcinogenicity to humans.
Reproductive toxicity	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Specific target organ toxicit	y - repeated exposure
STOT - repeated exposure	Based on available data the classification criteria are not met.
Aspiration hazard	
Aspiration hazard	Based on available data the classification criteria are not met.
Formald	lehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700
Acute toxicity - oral	
Notes (oral LD₅₀)	LD₅₀ >2000 mg/kg, Oral, Rat
Acute toxicity - inhalation	
Notes (inhalation LC₅₀)	Not applicable.
Specific target organ toxicit	y - single exposure
STOT - single exposure	Not available.

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Acute toxicity - oral	
Acute toxicity oral (LD₅₀ mg/kg)	17,100.0
Species	Rat
ATE oral (mg/kg)	17,100.0
Acute toxicity - dermal	
Notes (dermal LD₅₀)	Not applicable.
Acute toxicity - inhalation	
Notes (inhalation LC₅₀)	Not applicable.
Skin corrosion/irritation	
Animal data	Moderately irritating.
Serious eye damage/irritati	on
Serious eye damage/irritation	Causes serious eye irritation.
Skin sensitisation	
Skin sensitisation	Severe skin irritation.
	CARBON BLACK
Acute toxicity - oral	
Notes (oral LD ₅₀)	LD₅₀ >8000 mg/kg, Oral, Rat
Germ cell mutagenicity	
Summary	In vivo mutagenicity in rats occurs by mechanisms secondary to a threshold effect and is a consequence of "lung overload," which leads to chronic inflammation and the release of genotoxic oxygen species. This mechanism is considered to be a secondary genotoxic effect and, thus, carbon black itself would not be considered to be mutagenic.
Genotoxicity - in vitro	Carbon black is not suitable to be tested directly in bacterial (Ames test) and other in vitro systems because of its insolubility. However, when organic solvent extracts of carbon black have been tested, results showed no mutagenic effects. Organic solvent extracts of carbon black can contain traces of polycyclic aromatic hydrocarbons (PAHs). A study to examine the bioavailability of these PAHs showed that they are very tightly bound to carbon black and are not bioavailable (Borm, 2005).
Genotoxicity - in vivo	In an experimental investigation, mutational changes in the hprt ene were reported in alveolar epithelial cells in the rat following inhalation exposure to carbon black (Driscoll, 1997). This observation is considered to be rat-specific and a consequence of "lung overload," which leads to chronic inflammation and release of reactive oxygen species. This is considered to be a secondary genotoxic effect and, thus, carbon black itself would not be considered to be mutagenic.
Carcinogenicity	
IARC carcinogenicity	IARC Group 2B Possibly carcinogenic to humans.

SECTION 12: Ecological information		
Ecotoxicity		Dangerous for the environment. May cause long-term adverse effects in the aquatic environment.
Ecological i	nformation on ingre	edients.
		bis-[4-(2,3-epoxipropoxi)phenyl]propane
	Ecotoxicity	Toxic to aquatic life.
12.1. Toxici	t <u>y</u>	
Ecological i	nformation on ingre	edients.
		bis-[4-(2,3-epoxipropoxi)phenyl]propane
	Toxicity	WGK 2
	Acute aquatic tox	cicity
	Acute toxicity - fis	sh LC₅₀, 96 hours: 1.3 mg/l, Fish
	Acute toxicity - ac invertebrates	quatic EC ₅₀ , 48 hours: 2.1 mg/l, Ceriodaphnia dubia (water flea)
	Acute toxicity - ac plants	quatic EC₅₀, 72 hours: 11 mg/l, Algae
		Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700
	Acute aquatic tox	sicity
	Acute toxicity - fis	sh LC₅₀, 96 hours: 2.54 mg/l, Fish
	Acute toxicity - ac invertebrates	quatic EC₅₀, 48 hours: 2.55 mg/l, Daphnia magna
	Acute toxicity - ac plants	quatic EC₅₀, 72 hours: >1000 mg/l, Algae
		oxirane, mono[(C12-14-alkyloxy)methyl] derivs.
	Acute aquatic tox	cicity
	Acute toxicity - fis	sh LC50, 96 hours: > 1.8 mg/l, Oncorhynchus mykiss (Rainbow trout)
	Acute toxicity - ac invertebrates	quatic EC₅₀, 48 hours: 7.2 mg/l, Daphnia magna
	Acute toxicity - ac plants	quatic EC₅₀, 72 hours: ~ 844 mg/l, Freshwater algae
12.2. Persis	stence and degrada	ability
Persistence	and degradability	There are no data on the degradability of this product.
Ecological i	nformation on ingre	edients.
		bis-[4-(2,3-epoxipropoxi)phenyl]propane
	Biodegradation	Not readily biodegradable.
		Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700

Persistence and degradability	Not readily biodegradable.
12.3. Bioaccumulative potentia	al
Bioaccumulative potential	No data available on bioaccumulation.
Partition coefficient	Not available.
Ecological information on ingre	edients.
	bis-[4-(2,3-epoxipropoxi)phenyl]propane
Bioaccumulative	potential log Pow: 2.65 - 3.78, BCF: 3 - 31 31.00,
	Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700
Bioaccumulative	potential log Pow: 3.3, BCF: 150 150.00,
12.4. Mobility in soil	
Mobility	No data available.
12.5. Results of PBT and vPvI	3 assessment
Results of PBT and vPvB assessment	This substance is not classified as PBT or vPvB according to current EU criteria.
12.6. Other adverse effects	
Other adverse effects	Not known.
SECTION 13: Disposal consid	erations
13.1. Waste treatment method	ls
General information	Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
.	
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Avoid the spillage or runoff entering drains, sewers or watercourses.
Disposal methods Waste class	local Waste Disposal Authority. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Avoid the spillage or runoff
	local Waste Disposal Authority. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Avoid the spillage or runoff entering drains, sewers or watercourses. EWC NUMBER : Allocation of a waste code number in accordance with the European Waste Catalogue, should be carried out in agreement with an EA authorised waste disposal company.
Waste class	local Waste Disposal Authority. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Avoid the spillage or runoff entering drains, sewers or watercourses. EWC NUMBER : Allocation of a waste code number in accordance with the European Waste Catalogue, should be carried out in agreement with an EA authorised waste disposal company.

Air transport notes	A197 - These substances when carried in Single or Combination packaging's containing a net Qty per single or inner packaging of 5ltr or less for liquids or having a net mass per single or inner packaging of 5kg or less for solids, are not subject to any other provisions of these regulations provided the packaging's meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8

14.1. UN number

UN No. (ADR/RID)	3082
UN No. (IMDG)	3082
UN No. (ICAO)	3082
UN No. (ADN)	3082

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Bisphenol F Mixture)
Proper shipping name (IMDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Bisphenol F Mixture)
Proper shipping name (ICAO)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Bisphenol F Mixture)
Proper shipping name (ADN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Bisphenol F Mixture)

14.3. Transport hazard class(es)

ADR/RID class	9
ADR/RID classification code	M6
ADR/RID label	9
IMDG class	9
ICAO class/division	9
ADN class	9

Transport labels

14.4. Packing group	
ADR/RID packing group	Ш
IMDG packing group	Ш
ADN packing group	Ш
ICAO packing group	Ш

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

14.6. Special precautions for user

EmS	F-A, S-F	
ADR transport category	3	
Emergency Action Code	•3Z	
Hazard Identification Number (ADR/RID)	90	
Tunnel restriction code	(E)	
14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code		
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.	
SECTION 15: Regulatory information		
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture		
National regulations	Control of Substances Hazardous to Health Regulations 2002 (as amended).	

EU legislation	Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.
Guidance	A guide to local exhaust ventilation (LEV) HSG258 (as ammended) Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

Not applicable.

SECTION 16: Other information

Revision date	14/02/2022
Revision	8
Supersedes date	15/08/2019
SDS number	40180
Hazard statements in full	 H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects.

The information contained within this document is presented in good faith and is believed to be correct. West and Senior Limited makes no representation as to the accuracy and/or completeness of this information. This information is issued on the condition that the user will determine the safety and suitability of products for their purposes prior to use. All technical details and values presented are deemed typical and do not constitute a delivery specification.